



NOTES:

- 1 APPLY LOCTITE 242 P/N: 505016 TO THREADED JOINTS.
 2 APPLY GREASE P/N: 620030 TO SPLIT RINGS.
 3 APPLY WARNING STICKER P/N: 590273 TO ANVIL HOLDER.
 DO NOT ALLOW STICKER TO OVERLAP ON ANVIL.
 4 TORQUE JAM NUT TO 90-100 LBS-FT



127918	1	SPLIT RINGS	6
127984	1	SPINDLE BOLT	5
124286	1	JAM NUT	4
127985	1	ANVIL HOLDER	3
127987	1	THIMBLE	2
126154	1	ANVIL	1
PART NO.	ITEM	DESCRIPTION	ITEM

FORM KE104 Rev C				By accepting this proprietary Huck drawing, recipient agrees not to reproduce or disclose any part thereof to any other without the written permission of Huck International, Inc.			
MATERIAL:	-	SPEC:	-	TOLERANCES UNLESS OTHERWISE SPECIFIED: (ALL DIMENSIONS ARE IN INCHES)		HUCK INTERNATIONAL, INC., I.S.D. 1 CORPORATE DR., P.O. BOX 2270 KINGSTON, NEW YORK 12401	
HARDNESS:	-	(RAW OR STOCKED STATE)	-				
HEAT TREAT TO:	-	SPEC:	-	.XX, .XXX ±	.01, .005	ASSY, NOSE MHS-12 HSSFT-M12 TOOL	
SURFACE TREAT:	-	SPEC:	-	INT. COR. RADII	.005-.015		
SURFACE FINISH NOT TO EXCEED: 125 Ra				BREAK EDGES	.005-.015	DET: TRK	OK:
IDENTIFICATION PER SPEC 42-311: ★ PERMANENT				ANGLES ±	3°	DATE: 9/30/05	SCALE: 1:1
SURFACES TO BE ☉, //, ⊕, ⊥, & ▱ WITHIN .005 T.I.R.				FINAL ASSY:		FOC. FAC.	B

99-7700