


REV	DESCRIPTION	DET	DATE
A	RELEASE	EL	11/3/13
B	505717 WAS 507515	EL	1/24/14



NOTES:

- 1 MAXIMUM RECOMMENDED STROKE .500
- 2 FOR USE WITH THE 225/245 TOOL, USE ATTACHMENT P/N 119400-1 AND STROKE LIMITER 118362
- 3 FOR USE WITH 2500, USE ATTACHMENT P/N 119400-1 AND STROKE LIMITER KIT 119888
- 4 FOR OTHER TOOLS AND/OR OTHER TOOL AND STROKE COMBINATIONS, CONSULT ENGINEERING DEPARTMENT
- 5 SHIP WITH STOP 126747
- 6 SHIP WITH DEFLECTOR 126748-1
- 7 APPLY LOCTITE 243 TO SCREW THREADS

508511	2	#6-32 B.H.C.S.	13
126748-1	1	DEFLECTOR	12
130476	1	DRAWBAR	11
130474-C4	1	COLLET	10
130326	1	GUARD	9
120095	1	DEFLECTOR	8
122912	1	BARBED RETAINERS	7
122449	1	LOCATOR	6
505717	1	SPRING, COMPRESSION	5
118207	1	FOLLOWER	4
130256	1	CHUCK JAWS	3
130322	1	TOP GUARD	2
130471-C4	1	ANVIL	1
PART NO.	QTY	DESCRIPTION	ITEM

IDENTIFICATION PER SPEC 42-311: ★ ETCH	HUCK INTERNATIONAL, INC., I.S.D 1 CORPORATE DR KINGSTON, NEW YORK 12401		
ITAR/ECCN: EAR99	NOSE ASSEMBLY 5mm OFFSET - C4		
SCH B#: 8467.99.0190	FINAL ASSY:		
HTS: 8467.99.0190	ENG: NDG	DATE: 10/7/13	SCALE: 2:1
	B	RR-3701-C4	