

**Alcoa
Fastening
Systems**



Industrial Distribution Group



Marson®

Rivets, rivet nuts and
installation tools



Table of Contents

Introduction.....	2
General Information — Blind Rivets.....	3
Design Information	4
Steel Rivets.....	5
Aluminum Rivets.....	6
Aluminum/Steel Rivets.....	7
Stainless Rivets	8
Stainless/Steel Rivets	9
Closed-End Rivets.....	10
Multi-Grip Rivets.....	11
Specialty Rivets.....	12
Copper/Brass Rivets.....	12
Copper/Steel Rivets.....	12
Tri-Bulb Rivets.....	12
Painted Rivets.....	12
Back-Up Washers.....	12
Steel Q-Lok Rivets.....	13
T-Rivets/Klik-Split®.....	13
Automotive/Special Application Rivets.....	13
Klik-Lock™ Rivets.....	14, 15
Plastic Rivets	16
Plastic Rivet Tools	17
Hand Rivet Tools and Kits	18, 19
Air/Hydraulic Rivet Tools	20
Riveter Capacity Chart.....	21
Air/Hydraulic Tool Dimensions.....	21
Air/Hydraulic Tool Specifications.....	21
Rivet Nut Introduction.....	22
General Information-Rivet Nuts.....	23
MRN Series.....	24
MPN / MTS Series.....	25
MLR Series	26
MLC Series	27
MSR Series.....	28
MSC Series.....	29
MHN Series	30
MQN / MXN Series.....	31
MET Series	32
MNN Series.....	33
Rivet Nut Tools and Kits.....	34-38
Conversion Chart.....	39



Alcoa Fastening Systems-Industrial Distribution Group (AFS-IDG) offers the broadest line of blind fasteners for industrial applications in the industry. The breadth of the line is supported by a nationwide network of independent stocking warehouses, maintaining inventories that can deliver product to customers within hours if necessary. In short, the company's responsiveness to its customers and the needs of industry is second to none.

In an ongoing effort to be the best, AFS-IDG offers custom services such as painting, plating, anodizing, packaging, bar-coding and labeling. Add to this a strong commitment to research, design and development and you have an unbeatable combination.

Quality Policy

Alcoa Fastening Systems (AFS) is committed to satisfying our customers by delivering safe and reliable products and services. Marson Brand rivets are engineered in accordance with and governed by the Industrial Fastener Institute quality standards. AFS Acuna Operations is committed to the highest quality products and operating systems and employs Quality Management Systems certified to ISO 9001:2000.

We will achieve business excellence by:

- Encouraging and expecting the creative involvement of every employee.
- Listening to our customers and meeting their needs.
- Continuously improving our processes, products and services.

General Information — Blind Rivets

Rivet Styles

Open End



- For blind fastening where there is no access to opposite side of work
- Simple to install
- Wide variety of head styles and lengths available from 3/32" to 1/4" diameters

Closed End



- Moisture-resistant due to closed end
- Greater shear and tensile strength
- Mandrel is retained 100% of time
- 1/8" to 1/4" diameters

Multi-Grip



- Extended grip range capacity
- Reduces inventory (fewer sizes required)
- Use as a standard open end rivet
- 1/8" to 3/16" diameters

Tri-Bulb



- Large footprint on blind side
- Multi-grip capability
- Oversized hole tolerant
- Great for soft or brittle materials
- Available in 5/32" to 3/16" diameters

Q-Lok



- Retained mandrel increases shear and tensile strength
- Use in high vibration applications
- Mandrel breaks flush when used in mid-grip range
- Moisture-resistant due to tight seal
- 3/16" diameter

Klik-Lock



- Permanently retained mandrel provides increased shear and tensile values
- Use in high vibration applications
- Provides weather-resistant joint
- Available in 3/16" and 1/4" diameters

T-Rivets



- High clamp up
- High shear strength
- Creates a wide bearing surface
- 1/4" diameter

Special Application Rivets



- Small flange rivet used primarily for fastening decorative materials on boats, automobiles, trucks & other motor vehicles
- Best suited to applications where a discreet, secure installation of non-critical components is needed.

Plastic



- Precision-molded, all-nylon
- Secure lock prevents pull-out
- Fasten plastic to plastic, plastic to metal or plastic to fiberglass

Materials Available

Steel/steel, Aluminum/aluminum
Aluminum/steel, Stainless/stainless
Stainless/steel, Copper/brass, Copper/steel

Aluminum/steel, Aluminum/aluminum,
Stainless/stainless

Aluminum/steel, Steel/steel

Aluminum/aluminum

Steel/steel

Steel/steel, Aluminum/aluminum,
Stainless/stainless

Aluminum/steel

Stainless/steel, Aluminum/aluminum

Nylon body, Delrin 500 Mandrel

Head Styles

Buttonhead



- Low profile head diameter is twice the rivet body diameter, providing adequate bearing surface for nearly all applications
- Open-end buttonhead rivets offer the broadest selection of sizes available.

Large Flange



- Provides greater bearing surface for fastening soft and brittle facing materials and oversize facing holes
- Works well with soft materials, where the increased flange diameter protects the integrity of the application

Countersunk



- 120° countersunk rivets for applications where flush appearance is required

Alcoa Fastening Systems offers a full line of Marson brand rivets for general consumer and industrial applications. These easy-to-use rivets are used to fasten together two or more pieces of material of varying thickness.

Design Information

AFS Code Descriptions

Example: **ABL6-6A**

A – First Letter.....Rivet material (A = Aluminum, S = Steel, C = Copper, SS = Stainless Steel)

B – Second Letter.....Style of Head (B = Buttonhead, C = Countersunk)

L – Third Letter (if any).....Large Flange Head

6 – First Number.....Body Diameter in 32nds

6 – Second Number.....Maximum Grip Length in 16th's

A – Final Letter.....A = Aluminum Mandrel, S = Stainless Steel Mandrel, B = Brass Mandrel, C = Copper-plated Steel Mandrel, CLD = Closed-End

MG = Multi-Grip, QL = Q-Lok, KL = Klik-Lock

ATB = All Aluminum Tri-Bulb rivet. No letter indicates steel mandrel.

Design Information

1. The shear and tensile strength of the rivet selected and the number of rivets used in the application should equal or exceed the joint strength requirements. Typical ultimate shear and tensile strengths are listed by diameter and material on pages 5 through 16 of this catalog. Testing is recommended before final selection and use in product.
2. The rivet body material should be compatible with the materials to be joined to resist galvanic corrosion which may result in reduction of joint strength. If dissimilar materials are widely separated on the galvanic chart, it is advisable to separate them with a dielectric material such as paint or other coating. AFS can paint colors to match, as well as anodize or plate to your specifications.
3. After determination of strengths required by diameter and material, the total thickness of materials to be joined must be considered. The grip range for each rivet is listed on pages 5 through 16. Select the rivet grip range which includes the total thickness of materials to be joined. Please note that the rivet barrel length (Column L) is not the grip range.
4. Use recommended hole sizes for each rivet as shown on pages 5-16. An undersize hole will not allow insertion of rivet body. An oversize hole may cause rivet failure, joint failure and could adversely affect rivet shear and tensile strengths.
5. The various head styles (illustrated page 3) are offered to accommodate different assembly needs. The most popular Klik-Fast rivet is the buttonhead, whose lower-profile head is twice the diameter of the rivet body. This provides adequate bearing surface for nearly all applications. The large flange Klik-Fast rivet provides greater bearing surface for fastening soft or brittle facing materials. The countersunk Klik-Fast rivet is available for applications where a flush appearance is required.
6. Please visit us at AFS-IDG.com and e-mail your questions. We will follow up with evaluations, recommendations and testing if required.
 - Samples are available upon request.
 - Special packaging available.



To install


- 1 Insert rivet mandrel in rivet setting tool.




- 2 Using tool as a guide, insert rivet into prepared hole.




- 3 Or insert rivet into prepared hole and then engage the mandrel with rivet-setting tool. Squeeze trigger or handles to set rivet. Mandrel ejects after rivet is set.



Blind rivet benefits





Steel Rivets

Plated-Steel Rivet • Coated Steel Mandrel • IFI Grade 30

Buttonhead

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)					Inch	(mm)	Shear	Tensile
SB3-2	M50100	.020-.125	.5-3.2	3/32" (.094)	#41 (.097-.100)	.188	.032	.250	6.4	160	200
SB3-4	M50102	.126-.250	3.3-6.4	2.4	(2.46-2.54)	4.78	.810	.375	9.5	711	889
SB4-1	M50111	.020-.062	.5-1.6	1/8" (.125)	#30 (.129-.133)	.250	.040	.212	5.4	305	410
SB4-2	M50112	.063-.125	1.7-3.2	3.2	(3.28-3.38)	6.35	1.02	.275	7.0	1356	1823
SB4-3	M50115	.126-.187	3.3-4.8					.337	8.6		
SB4-4	M50117	.188-.250	4.9-6.4					.400	10.2		
SB4-5	M50120	.251-.312	6.5-7.9					.462	11.7		
SB4-6	M50121	.313-.375	8.0-9.5					.525	13.4		
SB4-8	M50122	.376-.500	9.6-12.7					.650	16.5		
SB4-10	M50125	.501-.625	12.8-15.9					.775	19.7		
SB5-2	M50132	.020-.125	.5-3.2	5/32" (.156)	#20 (.160-.164)	.312	.050	.300	7.6	420	600
SB5-3	M50134	.126-.187	3.3-4.8	4.0	(4.06-4.16)	7.92	1.27	.362	9.2	1868	2668
SB5-4	M50135	.188-.250	4.9-6.4					.425	10.8		
SB5-6	M50136	.251-.375	6.5-9.5					.550	14.0		
SB5-8	M50137	.376-.500	9.6-12.7					.675	17.2		
SB5-10	M50131	.501-.675	12.8-17.1					.800	20.3		
SB5-12	M50133	.676-.750	17.2-19.1					.925	23.5		
SB6-2	M50145	.020-.125	.5-3.2	3/16" (.187)	#11 (.192-.196)	.375	.060	.325	8.3	610	870
SB6-4	M50147	.126-.250	3.3-6.4	4.8	(4.88-4.98)	9.53	1.52	.450	11.5	2713	3889
SB6-6	M50149	.251-.375	6.5-9.5					.575	14.6		
SB6-8	M50152	.376-.500	9.6-12.7					.700	17.8		
SB6-10	M50155	.501-.625	12.8-15.9					.825	21.0		
SB6-12	M50159	.626-.750	16.0-19.1					.950	24.2		
SB6-14	M50163	.751-.875	19.2-22.2					1.075	27.3		
SB6-16	M50170	.876-1.000	22.3-25.4					1.200	30.5		
SB8-2	M50179	.020-.125	.5-3.2	1/4" (.250)	F (.257-.261)	.500	.080	.375	9.4	1270	1550
SB8-4	M50181	.126-.250	3.3-6.4	6.4	(6.53-6.63)	12.70	2.03	.500	12.7	5649	6894
SB8-6	M50183	.251-.375	6.5-9.5					.625	15.9		
SB8-8	M50185	.376-.500	9.6-12.7					.750	19.1		
SB8-10	M50187	.501-.625	12.8-15.9					.875	21.0		
SB8-12	M50189	.626-.750	16.0-19.1					1.000	25.4		
SB8-14	M50188	.751-.875	19.2-22.2					1.125	28.6		
SB8-16	M50190	.876-1.000	22.3-25.4					1.250	31.8		

Large Flange

SBL4-2	M50114	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.375	.065	.275	7.0	305	410
SBL4-3	M50124	.126-.187	3.3-4.8	3.2	(3.28-3.38)	9.53	1.65	.337	8.6	1356	1823
SBL4-4	M50119	.188-.250	4.9-6.4					.400	10.2		
SBL4-6	M50108	.313-.375	8.0-9.5					.525	13.3		
SBL4-8	M50109	.376-.500	9.6-12.7					.650	16.5		
SBL5-4	M50138	.188-.250	4.9-6.4	5/32" (.156)	#20 (.160-.164)	.468	.070	.425	10.8	420	600
SBL5-6	M50139	.251-.375	6.5-9.5	4.0	(4.06-4.16)	11.90	1.77	.550	14.0	1868	2668
SBL5-8	M50110	.376-.500	9.6-12.7					.675	17.2		
SBL6-4	M50148	.126-.250	3.3-6.4	3/16" (.187)	#11 (.192-.196)	.615	.090	.450	11.5	610	870
SBL6-6	M50150	.251-.375	6.5-9.5	4.8	(4.88-4.98)	15.88	2.28	.575	14.6	2713	3869
SBL6-8	M50153	.376-.500	9.6-12.7					.700	17.8		
SBL6-10	M50156	.501-.625	12.8-15.9					.825	21.0		
SBL6-12	M50160	.626-.750	16.0-19.1					.950	24.2		
SBL6-14	M50165	.751-.875	19.2-22.2					1.075	27.3		
SBL6-16	M50167	.876-1.000	22.3-25.4					1.200	30.5		


120° Countersunk

SC4-2	M50113	.092-.125	2.3-3.2	1/8" (.125)	#30 (.129-.133)	.220	.031 REF	.275	7.0	305	410
SC4-3	M50116	.126-.187	3.3-4.8	3.2	(3.28-3.38)	5.59	1.14	.337	8.6	1356	1823
SC4-4	M50118	.188-.250	4.9-6.4					.400	10.2		
SC4-6	M50126	.313-.375	6.5-9.5					.525	13.3		
SC4-8	M50127	.376-.500	9.6-12.7					.650	16.5		
SC5-4	M50140	.188-.250	4.9-6.4	5/32" (.156)	#20 (.160-.164)	.281	.040 REF	.425	10.8	420	600
				4.0	(4.06-4.16)	7.20	1.20			1868	2668
SC6-4	M50151	.151-.250	3.8-6.4	3/16" (.187)	#11 (.192-.196)	.350	.050 REF	.450	11.4	610	870
SC6-6	M50129	.251-.375	6.5-9.5	4.8	(4.88-4.98)	8.89	1.27	.575	14.6	2713	3869

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

** Also available in various packaged quantities.

Aluminum Rivets



5052 Aluminum Rivet • Aluminum Mandrel • IFI Grade 11 Buttonhead

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)	(mm)	(mm)	(mm)	(mm)	Inch	(mm)	Shear	Tensile
AB3-2A	M50200	.020-.125	.5-3.2	3/32" (.094)	#41 (.097-.100)	.188	.032	.250	6.4	80	120
AB3-4A	M50202	.126-.250	3.3-6.4	2.4	(2.46-2.54)	4.78	.810	.375	9.5	355	533
AB4-1A	M50211	.020-.062	.5-1.6	1/8" (.125)	#30 (.129-.133)	.250	.040	.212	5.4	155	240
AB4-2A	M50212	.063-.125	1.7-3.2	3.2	(3.28-3.38)	6.35	1.02	.275	7.0	689	1067
AB4-3A	M50215	.126-.187	3.3-4.8					.337	8.6		
AB4-4A	M50217	.188-.250	4.9-6.4					.400	10.2		
AB4-5A	M50220	.251-.312	6.5-7.9					.462	11.7		
AB4-6A	M50221	.313-.375	8.0-9.5					.525	13.4		
AB4-8A	M50222	.376-.500	9.6-12.7					.650	16.5		
AB4-10A	M50225	.501-.625	12.8-15.9					.775	19.7		
AB5-2A	M50232	.020-.125	.5-3.2	5/32" (.156)	#20 (.160-.164)	.312	.050	.300	7.6	230	340
AB5-3A	M50234	.126-.187	3.3-4.8	4.0	(4.06-4.16)	7.92	1.27	.362	9.2	1023	1512
AB5-4A	M50235	.188-.250	4.9-6.4					.425	10.8		
AB5-6A	M50236	.251-.375	6.5-9.5					.550	14.0		
AB5-8A	M50237	.376-.500	9.6-12.7					.675	17.2		
AB5-10A	M50238	.501-.625	12.8-17.1					.800	20.3		
AB5-12A	M50239	.626-.750	17.2-19.1					.925	23.5		
AB6-2A	M50245	.020-.125	.5-3.2	3/16" (.187)	#11 (.192-.196)	.375	.060	.325	8.3	330	515
AB6-4A	M50247	.126-.250	3.3-6.4	4.8	(4.88-4.98)	9.53	1.52	.450	11.5	1467	2290
AB6-6A	M50249	.251-.375	6.5-9.5					.575	14.6		
AB6-8A	M50252	.376-.500	9.6-12.7					.700	17.8		
AB6-10A	M50255	.501-.625	12.8-15.9					.825	21.0		
AB6-12A	M50259	.626-.750	16.0-19.1					.950	24.2		
AB6-14A	M50263	.751-.875	19.2-22.2					1.075	27.3		
AB6-16A	M50266	.876-1.000	22.3-25.4					1.200	30.5		
AB8-4A	M52281	.126-.250	3.3-6.4	1/4" (.250)	F (.257-.261)	.500	.080	.500	12.7	600	800
AB8-6A	M52283	.251-.375	6.5-9.5	6.4	(6.53-6.63)	12.70	1.88	.625	15.9	2668	3558
AB8-8A	M52285	.376-.500	9.6-12.7					.750	19.1		
AB8-10A	M52287	.501-.625	12.8-15.9					.875	21.0		
AB8-12A	M52289	.626-.750	16.0-19.1					1.000	25.4		
AB8-14A	M52288	.751-.875	19.2-22.2					1.125	28.6		

Large Flange


ABL4-2A	M50214	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.375	.065	.275	7.0	155	240
ABL4-3A	M50224	.126-.187	3.3-4.8	3.2	(3.28-3.38)	9.53	1.14	.337	8.6	689	1067
ABL4-4A	M50219	.188-.250	4.9-6.4					.400	10.2		
ABL4-6A	M50226	.313-.375	8.0-9.5					.525	13.3		
ABL4-8A	M50227	.376-.500	9.6-12.7					.650	16.5		
ABL5-4A	M50244	.188-.250	4.9-6.4	5/32" (.156)	#20 (.160-.164)	.468	.070	.425	10.8	230	340
				4.0	(4.06-4.16)	11.90	1.20			1023	1512
ABL6-4A	M50248	.126-.250	3.3-6.4	3/16" (.187)	#11 (.192-.196)	.615	.090	.450	11.5	330	515
ABL6-6A	M50250	.251-.375	6.5-9.5	4.8	(4.88-4.98)	15.88	2.28	.575	14.6	1467	2290
ABL6-8A	M50253	.376-.500	9.6-12.7					.700	17.8		
ABL6-10A	M50256	.501-.625	12.8-15.9					.825	21.0		
ABL6-12A	M50260	.626-.750	16.0-19.1					.950	24.2		
ABL6-16A	M50267	.875-1.00	22.2-25.4					1.200	30.5		

120° Countersunk

AC4-2A	M50213	.092-.125	2.3-3.2	1/8" (.125)	#30 (.129-.133)	.220	.031 REF	.275	7.0	155	240
AC4-3A	M50216	.126-.187	3.3-4.8	3.2	(3.28-3.38)	5.59	1.14	.337	8.6	689	1050
AC4-4A	M50218	.188-.250	4.9-6.4					.400	10.2		
AC4-6A	M50241	.313-.375	8.0-9.5					.525	13.3		
AC5-4A	M50240	.188-.250	4.9-6.4	5/32" (.156)	#20 (.160-.164)	.281	.040 REF	.425	10.8	230	340
AC5-6A	M50242	.313-.375	8.0-9.5	4.0	(4.06-4.16)	7.20	1.20	.550	14.0	1020	1512
AC6-4A	M50251	.151-.250	3.8-6.4	3/16" (.187)	#11 (.192-.196)	.350	.050 REF	.407	10.3	330	515
AC6-6A	M50229	.251-.375	6.5-9.5	4.8	(4.88-4.98)	8.89	1.27	.575	14.6	1467	2290
AC6-8A	M50246	.376-.500	9.6-12.7					.700	17.8		

KLICK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

** Also available in various packaged quantities.



Aluminum/Steel Rivets

5056 Aluminum Rivet • Coated Steel Mandrel • IFI Grade 19

Buttonhead

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)					Inch	(mm)	Shear	Tensile
AB3-2	M50300	.020-.125	.5-3.2	3/32" (.094)	#41 (.097-.100)	.188	.032	.250	6.4	120	160
AB3-4	M50302	.126-.250	3.3-6.4	2.4	(2.46-2.54)	4.78	.810	.375	9.5	534	711
AB4-1	M50311	.020-.062	.5-1.6	1/8" (.125)	#30 (.129-.133)	.250	.040	.212	5.4	225	315
AB4-2	M50312	.063-.125	1.7-3.2	3.2	(3.28-3.38)	6.35	1.02	.275	7.0	1000	1401
AB4-3	M50315	.126-.187	3.3-4.8					.337	8.6		
AB4-4	M50317	.188-.250	4.9-6.4					.400	10.2		
AB4-5	M50320	.251-.312	6.5-7.9					.462	11.7		
AB4-6	M50321	.313-.375	8.0-9.5					.525	13.4		
AB4-8	M50322	.376-.500	9.6-12.7					.650	16.5		
AB4-10	M50325	.501-.625	12.8-15.9					.775	19.7		
AB5-2	M50332	.020-.125	.5-3.2	5/32" (.156)	#20 (.160-.164)	.312	.050	.300	7.6	300	470
AB5-3	M50334	.126-.187	3.3-4.8	4.0	(4.06-4.16)	7.92	1.27	.362	9.2	1334	2090
AB5-4	M50335	.188-.250	4.9-6.4					.425	10.8		
AB5-6	M50336	.251-.375	6.5-9.5					.550	14.0		
AB5-8	M50337	.376-.500	9.6-12.7					.675	17.2		
AB6-2	M50345	.020-.125	.5-3.2	3/16" (.187)	#11 (.192-.196)	.375	.060	.325	8.3	465	700
AB6-4	M50347	.126-.250	3.3-6.4	4.8	(4.06-4.16)	9.53	1.52	.450	11.5	2068	3113
AB6-6	M50349	.251-.375	6.5-9.5					.575	14.6		
AB6-8	M50352	.376-.500	9.6-12.7					.700	17.8		
AB6-10	M50355	.501-.625	12.8-15.9					.825	21.0		
AB6-12	M50359	.626-.750	16.0-19.1					.950	24.2		
AB6-16	M50366	.751-1.00	19.2-25.4					1.200	30.5		
AB8-4	M52381	.126-.250	3.3-6.4	1/4" (.250)	F (.257-.261)	.500	.080	.500	12.7	990	1195
AB8-6	M52383	.251-.375	6.5-9.5	6.4	(6.53-6.63)	12.70	1.88	.625	15.9	4403	5315
AB8-8	M52385	.376-.500	9.6-12.7					.750	19.1		
AB8-10	M52387	.501-.625	12.8-15.9					.875	21.0		
AB8-12	M52389	.626-.750	16.0-19.1					1.000	25.4		
AB8-14	M52388	.751-.875	19.2-22.2					1.125	28.6		
AB8-16	M52390	.876-1.000	22.3-25.4					1.250	31.8		

Large Flange

ABL4-2	M50314	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.375	.065	.275	7.0	225	315
ABL4-3	M50324	.126-.187	3.3-4.8	3.2	(3.28-3.38)	9.53	1.65	.337	8.6	1000	1401
ABL4-4	M50319	.188-.250	4.9-6.4					.400	10.2		
ABL4-6	M50326	.313-.375	8.0-9.5					.525	13.3		
ABL5-4	M50338	.126-.250	3.2-6.4	5/32" (.156)	#20 (.160-.164)	.468	.070	.425	10.8	300	470
				4.0	(4.06-4.16)	11.9	1.78			1334	2090
ABL6-4	M50348	.126-.250	3.3-6.4	3/16" (.187)	#11 (.192-.196)	.615	.090	.450	11.5	465	700
ABL6-6	M50350	.251-.375	6.5-9.5	4.8	(4.88-4.98)	15.88	2.08	.575	14.6	2068	3113
ABL6-8	M50353	.376-.500	9.6-12.7					.700	17.8		
ABL6-10	M50356	.501-.625	12.8-15.9					.825	21.0		
ABL6-12	M50360	.626-.750	16.0-19.1					.950	24.2		
ABL6-14	M50365	.751-.875	19.2-22.2					1.200	27.3		
ABL6-16	M50367	.876-1.000	22.3-25.4					1.450	30.5		


120° Countersunk

AC4-2	M50313	.092-.125	2.3-3.2	1/8" (.125)	#30 (.129-.133)	.220	.031 REF	.275	7.0	225	315
AC4-3	M50316	.126-.187	3.3-4.8	3.2	(3.28-3.38)	5.59	1.14	.337	8.6	1000	1401
AC4-4	M50318	.188-.250	4.9-6.4					.400	10.2		
AC4-5	M50323	.251-.312	6.5-9.5					.525	11.7		
AC5-4	M50340	.188-.250	4.9-6.4	5/32" (.156)	#20 (.160-.164)	.281	.040 REF	.425	10.8	300	470
AC5-6	M50342	.251-.375	6.5-9.5	4.0	(4.06-4.16)	7.2	1.20	.550	14.0	1334	2090
AC5-8	M50343	.376-.500	9.6-12.7					.675	17.2		
AC6-4	M50346	.151-.250	3.8-6.4	3/16" (.187)	#11 (.192-.196)	.350	.050 REF	.407	10.3	465	700
AC6-6	M50329	.251-.375	6.5-9.5	4.8	(4.88-4.98)	8.89	1.27	.575	14.6	2068	3113
AC6-8	M50306	.376-.500	9.6-12.7					.700	17.8		

KLIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

** Also available in various packaged quantities.

Stainless Rivets



Stainless Rivet • Stainless Mandrel • IFI Grade 51 Buttonhead

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)					Inch	(mm)	Shear	Tensile
SSB4-1S	M50411	.020-.062	.5-1.6	1/8" (.125)	#30 (.129-.133)	.250	.040	.212	5.4	520	600
SSB4-2S	M50412	.063-.125	1.7-3.2	3.2	(3.28-3.38)	6.35	1.02	.275	7.0	2310	2660
SSB4-3S	M50415	.126-.187	3.3-4.8					.337	8.6		
SSB4-4S	M50417	.188-.250	4.9-6.4					.400	10.2		
SSB4-5S	M50420	.251-.312	6.5-7.9					.462	11.7		
SSB4-6S	M50421	.313-.375	8.0-9.5					.525	13.4		
SSB4-8S	M50422	.376-.500	9.6-12.7					.650	16.5		
SSB5-2S	M50432	.020-.125	.5-3.2	5/32" (.156)	#20 (.160-.164)	.312	.045	.300	7.6	785	1040
SSB5-3S	M50434	.126-.187	3.3-4.8	4.0	(4.06-4.16)	7.92	1.14	.338	8.0	3490	4620
SSB5-4S	M50435	.188-.250	4.9-6.4					.425	10.8		
SSB5-6S	M50436	.251-.375	6.5-9.5					.550	14.0		
SSB5-8S	M50437	.376-.500	9.6-12.7					.675	17.2		
SSB5-10S	M50427	.501-.625	12.8-15.9					.800	20.3		
SSB6-2S	M50445	.020-.125	.5-3.2	3/16" (.187)	#11 (.192-.196)	.375	.066	.325	8.3	1150	1300
SSB6-4S	M50447	.126-.250	3.3-6.4	4.8	(4.88-4.98)	9.53	1.40	.450	11.5	5110	5780
SSB6-6S	M50449	.251-.375	6.5-9.5					.575	14.6		
SSB6-8S	M40450	.376-.500	9.6-12.7					.700	17.8		
SSB6-10S	M40457	.501-.625	12.8-15.9					.825	21.0		
SSB6-12S	M50458	.626-.750	16.0-19.1					.950	24.2		
SSB6-16S	M50466	.751-1.000	19.2-25.4					1.200	30.5		
SSB8-4S	M52481	.126-.250	3.3-6.4	1/4" (.250)	F (.257-.261)	.500	.074	.500	12.7	1700	2100
SSB8-6S	M52483	.251-.375	6.5-9.5	6.4	(6.53-6.63)	12.70	1.88	.625	15.9	7560	9340
SSB8-8S	M52485	.376-.500	9.6-12.7					.750	19.1		
SSB8-10S	M52487	.501-.625	12.8-15.9					.875	21.0		
SSB8-12S	M52489	.626-.750	16.0-19.1					1.000	25.4		

Large Flange


SSBL4-2S	M50409	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.375	.045	.275	7.0	520	600
SSBL4-3S	M50416	.126-.187	3.3-4.8	3.2	(3.28-3.38)	9.53	1.14	.337	8.6	2310	2660
SSBL4-4S	M50418	.188-.250	4.9-6.4					.400	10.2		
SSBL6-4S	M50452	.126-.250	3.3-6.4	3/16" (.187)	#11 (.192-.196)	.615	.082	.450	11.5	1150	1300
SSBL6-6S	M50453	.251-.375	6.5-9.5	4.8	(4.88-4.98)	15.88	2.08	.575	14.6	5110	5780
SSBL6-8S	M50456	.376-.500	9.6-12.7					.700	17.8		
SSBL6-10S	M50451	.501-.625	12.8-15.9					.825	21.0		
SSBL6-12S	M50455	.626-.750	16.0-19.1					.950	24.2		

120° Countersunk

SSC4-2S	M50423	.092-.125	2.3-3.2	1/8" (.125)	#30 (.129-.133)	.220	.031 REF	.275	7.0	520	600
SSC4-3S	M50424	.126-.187	3.3-4.8	3.2	(3.28-3.38)	5.59	1.14	.337	8.6	2310	2660
SSC4-4S	M50425	.188-.250	4.9-6.4					.400	10.2		
SSC4-5S	M50426	.251-.312	6.5-7.9					.462	11.7		
SSC6-4S	M50429	.151-.250	3.8-6.4	3/16" (.187)	#11 (.192-.196)	.350	.050 REF	.407	10.3	1150	1300
				4.8	(4.88-4.98)	8.89	1.27			5110	5780

KLIIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

** Also available in various packaged quantities.



Stainless/Steel Rivets

Stainless Rivet • Coated Steel Mandrel • IFI Grade 50

Buttonhead

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)					Inch	(mm)	Shear	Tensile
SSB4-1	M40511	.020-.062	.5-1.6	1/8" (.125)	#30 (.129-.133)	.250	.040	.212	5.4	520	600
SSB4-2	M40512	.063-.125	1.7-3.2	3.2	(3.28-3.38)	6.35	1.02	.275	7.0	2310	2660
SSB4-3	M40515	.126-.187	3.3-4.8					.337	8.6		
SSB4-4	M40517	.188-.250	4.9-6.4					.400	10.2		
SSB4-5	M40526	.251-.312	6.5-7.9					.462	11.7		
SSB4-6	M40521	.313-.375	8.0-9.5					.525	13.4		
SSB4-8	M40522	.376-.500	9.6-12.7					.650	16.5		
SSB5-2	M40532	.020-.125	.5-3.2	5/32" (.156)	#20 (.160-.164)	.312	.045	.300	7.6	785	1040
SSB5-4	M40535	.126-.250	3.3-6.4	4.0	(4.06-4.16)	7.92	1.14	.425	8.0	3490	4620
SSB5-6	M40536	.251-.375	6.5-9.5					.550	14.0		
SSB6-2	M40545	.020-.125	.5-3.2	3/16" (.187)	#11 (.192-.196)	.375	.055	.325	8.3	1150	1300
SSB6-4	M40547	.126-.250	3.3-6.4	4.8	(4.88-4.98)	9.53	1.40	.450	11.5	5110	5780
SSB6-6	M40549	.251-.375	6.5-9.5					.575	14.6		
SSB6-8	M40550	.376-.500	9.6-12.7					.700	17.8		
SSB6-10	M40557	.501-.625	12.8-15.9					.825	21.0		
SSB6-12	M40558	.626-.750	16.0-19.1					.950	24.2		
SSB6-16	M40566	.751-1.000	19.2-25.4					1.120	30.5		

Large Flange

SSBL4-2	M40513	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.375	.045	.275	7.0	520	600
SSBL4-3	M40518	.126-.187	3.3-4.8	3.2	(3.28-3.38)	9.53	1.14	.337	8.6	2310	2660
SSBL4-4	M40519	.188-.250	4.9-6.4					.400	10.2		
SSBL6-4	M40548	.126-.250	3.3-6.4	3/16" (.187)	#11 (.192-.196)	.615	.082	.450	11.5	1150	1300
SSBL6-6	M40553	.251-.375	6.5-9.5	4.8	(4.88-4.98)	15.88	2.08	.575	14.6	5110	5780
SSBL6-8	M40556	.376-.500	9.6-12.7					.700	17.8		
SSBL6-10	M40551	.501-.625	12.8-15.9					.825	21.0		
SSBL6-12	M40555	.626-.750	16.0-19.1					.950	24.2		


120° Countersunk

SSC4-2	M40523	.092-.125	2.3-3.2	1/8" (.125)	#30 (.129-.133)	.220	.031 REF	.275	7.0	520	600
SSC4-3	M40524	.126-.187	3.3-4.8	3.2	(3.28-3.38)	5.59	1.14	.337	8.6	2310	2660
SSC4-4	M40525	.188-.250	4.9-6.4					.400	10.2		
SSC4-5	M40528	.251-.312	6.5-7.9					.462	11.7		
SSC6-4	M40529	.151-.250	3.8-6.4	3/16" (.187)	#11 (.192-.196)	.350	.050 REF	.407	10.3	1150	1300
				4.8	(4.88-4.98)	8.89	1.27			5110	5780

KLIIK-FAST RIVETS conform to IFI-114 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

** Also available in various packaged quantities.

Closed-End Rivets



5056 Aluminum/Steel • IFI Grade 19 Buttonhead

AFS Description	Bulk Part No.**	Grip Range		Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)	(mm)	(mm)	(mm)	(mm)	Inch	(mm)	Shear	Tensile
AB4-1CLD	M56000	.020-.062	.5-1.6	1/8"(.126)	#30	.236	.050	.255	6.48	240	280
AB4-2CLD	M56001	.063-.125	1.7-3.2	3.2	(.129-.133)	5.99	1.27	.316	8.03	1060	1240
AB4-3CLD	M56002	.126-.187	3.3-4.8					.377	9.58		
AB4-4CLD	M56003	.188-.250	4.9-6.4					.440	11.18		
AB4-5CLD	M56004	.251-.312	6.5-7.9					.502	12.75		
AB4-6CLD	M56015	.313-.375	8.0-9.5					.565	14.35		
AB5-2CLD	M56005	.063-.125	1.7-3.2	5/32"(.157)	#20	.315	.065	.330	8.38	350	480
AB5-3CLD	M56006	.126-.187	3.3-4.8	4.0	(.160-.164)	8.00	1.65	.392	9.96	1550	2130
AB5-5CLD	M56007	.188-.312	4.9-7.9					.517	13.13		
AB6-2CLD	M56008	.063-.125	1.7-3.2	3/16"(.188)	#11	.374	.080	.345	8.76	500	690
AB6-4CLD	M56009	.126-.250	3.3-6.4	4.8	(.192-.196)	9.50	2.03	.470	11.94	2230	3070
AB6-6CLD	M56010	.251-.375	6.5-9.5					.595	15.11		
AB6-8CLD	M56011	.376-.500	9.6-12.7					.720	18.29		
AB6-10CLD	M56012	.501-.625	12.8-15.9					.845	21.46		
AB8-4CLD	M56013	.062-.250	1.6-6.4	1/4"(.252)	F	.512	.090	.505	12.83	900	1100
AB8-6CLD	M56014	.251-.375	6.5-9.5	6.4	(.257-.261)	13.0	2.29	.630	16.00	3950	5000

120° Countersunk

AC4-2CLD	M56016	.092-.125	2.3-3.2	1/8"(.126)	#30	.236	.050	.361	9.17	240	280
AC4-3CLD	M56017	.126-.187	3.3-4.8	3.2	(.129-.133)	5.99	1.27	.422	10.72	1060	1240
AC4-4CLD	M56018	.188-.250	4.9-6.4					.486	12.34		
AC6-4CLD	M56019	.126-.250	3.3-6.4	3/16"(.188)	#11	.374	.540	.540	13.72	500	690
				4.8	(.192-.196)	9.50	13.72			2230	3070

All Aluminum Buttonhead • IFI Grade 15

AB4-2ACLD	M56201	.063-.125	1.7-3.2	1/8"(.126)	#30	.236	.050	.316	8.03	99	108
AB4-3ACLD	M56202	.126-.187	3.3-4.8	3.2	(.129-.133)	5.99	1.27	.377	9.58	450	490
AB4-4ACLD	M56203	.188-.250	4.9-6.4								
AB5-4ACLD	M56207	.126-.250	3.3-6.4	5/32"(.157)	#20	.315	.065	.440	11.18	127	180
				4.0	(.160-.164)	8.00	1.65	.500	12.70	198	246
AB6-2ACLD	M56208	.063-.125	1.7-3.2	3/16"(.188)	#11	.374	.080	.345	8.76	900	1120
AB6-4ACLD	M56209	.126-.250	3.3-6.4	4.8	(.192-.196)	9.50	2.03	.417	11.94	3950	5090
AB6-6ACLD	M56210	.251-.375	6.5-9.5					.591	15.06		
AB6-8ACLD	M56211	.376-.500	9.6-12.7					.720	18.29		
AB6-10ACLD	M56022	.501-.625	12.8-15.9					.845	21.46		


All Stainless Buttonhead

SSB4-2SCLD	M56403	.063-.125	1.7-3.2	1/8"(.126)	#30	.236	.039	.346	8.79	441	551
SSB4-3SCLD	M56405	.126-.187	3.3-4.8	3.2	(.129-.133)	5.99	.990	.407	10.34	2000	2500
SSB4-4SCLD	M56406	.188-.250	4.9-6.4					.470	11.94		
SSB6-2SCLD	M56408	.063-.125	1.7-3.2	3/16"(.188)	#11	.374	.070	.375	9.52	991	1210
SSB6-4SCLD	M56409	.126-.250	3.3-6.4	4.8	(.192-.196)	9.49	1.77	.500	12.70	4500	5500
SSB6-6SCLD	M56410	.251-.375	6.5-9.5					.625	15.87		
SSB6-8SCLD	M56411	.376-.500	9.6-12.7					.750	19.05		
SSB6-10SCLD	M56412	.501-.625	12.8-15.9					.875	22.22		

Note: A slightly smaller mandrel diameter is required for closed-end rivets; therefore when setting closed-end rivets using Marson brand rivet setting tools, we recommend you use one size smaller nosepiece when possible (i.e., to set 1/8" rivets, use 3/32" nosepiece).

KLIK-FAST RIVETS conform to IFI-126 (inch). Millimeters (mm) and newtons (N) are in green.

**Also available in packaged quantities.



Multi-Grip Rivets

Buttonhead

Large Flange

Countersunk

Plated Steel Rivet • Steel Mandrel • IFI Grade 30

Steel Buttonhead

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch	Drill No. & Hole Size	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)	(mm)	(mm)	(mm)	(mm)	Inch	(mm)	Shear	Tensile
SB41-42MG	M56112	.043-.156	1.1-4.0	1/8"(.125)	#30(.129-.133)	.283	.033	.355	9.0	340	385
				3.2	(3.28-3.38)	.720	.850			1510	1710
SB52-53MG	M56134	.056-.196	1.4-5.0	5/32"(.156)	#20(.160-.164)	.319	.047	.433	11.0	440	530
				4.0	(4.06-4.16)	.810	1.20			1960	2360
SB62-63MG	M56146	.047-.187	1.2-4.8	3/16"(.187)	#11(.192-.196)	.386	.069	.405	10.3	810	750
				4.8	(4.88-4.98)	9.80	1.75			3605	3335
SB63-64MG	M56147	.156-.250	4.0-6.3					.500	12.7	1025	780
										4560	3470

Aluminum/Steel Buttonhead†

AB41-43MG	M56315	.031-.187	.8-4.8	1/8"(.125)	#30(.129-.133)	.250	.037	.315	8.0	165	230
AB42-44MG	M56317	.046-.250	1.2-6.4	3.2	(3.28-3.38)	6.35	.95	.375	9.5	735	1025
AB44-45MG	M56320	.156-.312	4.0-7.9					.438	11.1		
AB45-46MG	M56321	.216-.375	5.5-9.5					.500	12.7		
AB52-54MG	M56335	.046-.250	1.2-6.4	5/32"(.156)	#20(.160-.164)	.312	.047	.375	9.5	255	375
AB54-56MG	M56336	.156-.375	4.0-9.5	4.0	(4.06-4.16)	7.92	1.20	.500	12.7	1135	1670
AB56-58MG	M56337	.250-.500	6.4-12.7					.666	16.9		
AB62-64MG	M56347	.062-.250	1.6-6.4	3/16"(.187)	#11(.192-.196)	.386	.057	.406	10.3	350	530
AB63-67MG	M56351	.187-.437	4.8-11.1	4.8	(4.88-4.98)	9.80	1.45	.595	15.1	1560	2360
AB66-68MG	M56352	.250-.500	6.4-12.7					.666	16.9		
AB610-612MG	M56359	.500-.781	12.7-19.8					.978	24.8		

Aluminum/Steel Large Flange

ABL42-43MG	M56314	.031-.187	.8-4.8	1/8"(.125)	#30(.129-.133)	.325	.039	.315	8.0	165	230
ABL42-44MG	M56319	.046-.250	1.2-6.4	3.2	(3.28-3.38)	8.25	1.00	.375	9.5	735	1025
ABL44-45MG	M56322	.156-.312	4.0-7.9					.438	11.1		
ABL52-54MG	M56241	.062-.250	1.6-6.4	5/32"(.156)	#20(.160-.164)	.374	.051	.375	9.5	255	375
ABL53-55MG	M56340	.125-.312	3.2-7.9	4.0	(4.06-4.16)	9.50	1.30	.438	11.1	1135	1670
ABL55-58MG	M56342	.251-.500	6.4-12.7					.690	17.5		
ABL64-66MG	M56350	.062-.250	1.6-6.4	3/16"(.187)	#11(.192-.196)	.625	.069	.406	10.3	350	530
ABL66-68MG	M56353	.250-.500	6.4-12.7	4.8	(4.88-4.98)	15.85	1.75	.666	16.9	1560	2360
ABL610-612MG	M56360	.500-.781	12.7-19.8					.978	24.8		


Aluminum/Steel 120° Countersunk

AC43-44MG	M56318	.093-.250	2.4-6.4	1/8"(.125)	#30(.129-.133)	.209	.029 REF	.383‡	9.7	155	206
				3.2	(3.28-3.38)	5.30	.75			690	912
AC53-55MG	M56357	.109-.312	2.7-7.9	5/32"(.156)	#20(.160-.164)	.252	.049 REF	.470‡	11.9	255	300
				4.0	(4.06-4.16)	6.40	1.24			1135	1670
AC62-65MG	M56361	.062-.312	1.6-7.9	3/16"(.187)	#11(.192-.196)	.345	.051 REF	.500‡	12.7	350	530
AC66-68MG	M56362	.250-.500	6.4-12.7	4.8	(4.88-4.98)	8.75	1.30	.690‡	17.5	1560	2360

‡ Countersunk—Total Length (L) including head


Millimeters (mm) and newtons (N) are in green.

**Also available in packaged quantities.



Multi-grip rivets provide an effective and economical alternative to other, more costly methods of fastening, because one size handles the grip range capacity of up to 3 standard open end rivets. Multi-grip rivets can be used in any application requiring open end rivets, while reducing inventory requirements. Use multi-grip rivets as a standard open-end rivet . . . no special tool is needed.

Specialty Rivets




#110 Copper/Brass & #110 Copper/Steel (copper-plated mandrel)

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)					Inch	(mm)	Shear	Tensile
CB4-2B	M58600	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.250	.040	.275	7.0	215	300
CB4-4B	M58602	.188-.250	4.9-6.4	3/2	3.3 (3.28-3.38)	6.35	1.02	.400	10.2	950	1330
CB4-2C	M58600	.063-.125	1.7-3.2	1/8" (.125)	#30 (.129-.133)	.250	.040	.275	7.0	215	300
CB4-4C	M58602	.188-.250	4.9-6.4	3/2	3.3 (3.28-3.38)	6.35	1.02	.400	10.2	950	1330

B - Copper/Brass; C - Copper/Steel (copper-plated mandrel)

**Also available in packaged quantities.



Tri-Bulb Rivets

AFS Description	D	Grip Range	Drill No. & Hole Size	A	E	H	N	Y	Shear		Tensile	
									lbs.	newtons	lbs.	newtons
A0516ATB	5/32" (.156)	.039 - .118	#20 (.160-.164)	.091	.055	.315	.630	.236	134	600	224	1000
A0523ATB		.039 - .276		.091	.055	.315	.835	.335	134	600	224	1000
A0619ATB	3/16" (.187)	.039 - .157	#11 (.192-.196)	.115	.071	.386	.720	.276	202	900	269	1200
A0622ATB		.039 - .248		.115	.071	.386	.807	.335	202	900	269	1200
A0625ATB		.039 - .354		.115	.071	.386	.925	.374	202	900	269	1200
A0630ATB		.157 - .472		.115	.071	.386	1.063	.433	202	900	269	1200
AL0625ATB		.039 - .354		.115	.079	.551	.925	.374	202	900	269	1200

For black rivets add BL to the part number. White available as special order item. Refer to price list for bulk part number.

Painted Rivets*

W=White BR=Brown BL=Black

AFS Description	Bulk Part No.**	Rivet Color	Grip Range		D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
			Inch	(mm)					Inch	(mm)	Shear	Tensile
AB4-2AW	M53032	W	.062-.125	1.7-3.2	.125	#30 (.129-.133)	.250	.040	.275	7.0	155	240
AB4-3AW	M53007	W	.126-.187	3.2-4.8	3.2	(3.28-3.38)	6.35	1.02	.337	8.6	689	1067
AB4-4AW	M53009	W	.188-.250	4.9-6.4					.400	10.2		
AB4-2ABR	M53097	BR	.062-.125	1.7-3.2	.125	#30 (.129-.133)	.275	.040	.275	7.0	155	240
AB4-3ABR	M53081	BR	.126-.187	3.2-4.8	3.2	(3.28-3.38)	.337	1.02	.337	8.6	689	1067
AB4-4ABR	M53099	BR	.188-.250	4.9-6.4					.400	10.2		
AB4-2ABL	M53098	BL	.062-.125	1.7-3.2	.125	#30 (.129-.133)	.275	.040	.275	7.0	155	240
AB4-3ABL	M53102	BL	.126-.187	3.2-4.8	3.2	(3.28-3.38)	.337	1.02	.337	8.6	689	1067
AB4-4ABL	M53100	BL	.188-.250	4.9-6.4					.400	10.2		
SB4-2W	M53033	W	.062-.125	1.7-3.2	.125	#30 (.129-.133)	.275	.040	.275	7.0	305	410
SB4-3W	M53034	W	.126-.187	3.2-4.8	3.2	(3.28-3.38)	.337	1.02	.337	8.6	1356	1823
SB4-4W	M53036	W	.188-.250	4.9-6.4					.400	10.2		
SB4-2BR	M53003	BR	.062-.125	1.7-3.2	.125	#30 (.129-.133)	.275	.040	.275	7.0	305	410
SB4-3BR	M53011	BR	.126-.187	3.2-4.8	3.2	(3.28-3.38)	.337	1.02	.337	8.6	1356	1823
SB4-4BR	M53012	BR	.188-.250	4.9-6.4					.400	10.2		
SB4-2BL	M53060	BL	.062-.125	1.7-3.2	.125	#30 (.129-.133)	.275	.040	.275	7.0	330	515
SB4-4BL	M53051	BL	.188-.250	3.2-4.8	3.2	(3.28-3.38)		1.02	.400	10.2	1467	2290

*Custom colors available; contact factory for additional information. Painted rivets work best when hole size is at the high end of tolerance to allow for paint.

**Also available in packaged quantities.

Back-Up Washers

AFS Description	Standard Carton Qty.	Bulk Part No.**	500 Pack No.	Material	For Hole Size	Size/Shape
SS-3	5M	M50653	M40653	STEEL	3/32"	1/2" SQ
SS-4	5M	M50654	M40654	STEEL	1/8"	1/2" SQ
SS-6	5M	M50656	M40656	STEEL	3/16"	1/2" SQ
SS-8	10M	M50658	M40658	STEEL	1/8"	3/8" RD
SS-9	10M	M50655	M40655	STEEL	5/32"	7/16" RD
SS-10	10M	M50661	M40661	STEEL	3/16"	1/2" RD
SS-12	10M	M50662	M40662	STEEL	1/4"	1/2" RD
AS-8	10M	M50657	M40657	ALUMINUM	1/8"	3/8" RD
AS-9	10M	M50659	M40659	ALUMINUM	5/32"	7/16" RD
AS-10	10M	M50660	M40660	ALUMINUM	3/16"	1/2" RD
AS-12	10M	M50665	M40665	ALUMINUM	1/4"	1/2" RD

**Also available in packaged quantities.


Back-up washers are .056"-.062" thick. They are used when fastening soft materials or to compensate for oversize holes.



Double-Ended Drill Bit/M39100

This double-ended drill bit provides the correct size hole and angle for 1/8" diameter countersink rivets, drilling and countersinking in one operation.






Specialty Rivets

Steel Q-Lok™ Rivets

Plated Steel Body Plated Steel Mandrel

AFS Description	Bulk Part No.**	Grip Range		D Rivet Dia. Nom. Inch (mm)	Drill No. & Hole Size (mm)	H Head Dia. Nom. Inch (mm)	E Head Height Max. Inch (mm)	L Rivet Length Max.		Typical Ultimate Strength (lbs.) (newtons)	
		Inch	(mm)					Inch	(mm)	Shear	Tensile
SB6-2QL	M55145	.062-.125	2.3-3.2	3/16"(.187)	#11(.192-.196)	.375	.065	.350	8.9	1050	825
SB6-4QL	M55147	.126-.250	3.3-6.4	4.8	(4.88-4.98)	9.5	1.65	.475	12.0	4670	3670
SB6-6QL	M55149	.251-.375	6.5-9.5					.600	15.2		
SB6-8QL	M55152	.376-.500	9.6-12.7					.725	18.4		



T-Rivets/Klik-Split®

Aluminum/Steel†

—	M52372	.062-.125	1.58-3.18	1/4"(.250)	F(.257-.261)	.500	.120	.520	13.22	1500	1000
—	M52371	.032-.140	.81-3.56	6.4	(.653-6.63)	12.7	3.00	.520	13.22	6670	4445
—	M52368	.251-.312	6.38-7.93					.707	17.79		
—	M52369	.312-.375	7.95-9.53					.770	19.56		
—	M52370	.376-.437	9.55-11.10					.832	21.13		
—	M50376	.520-.620	13.21-15.97					.960	24.38		

† Requires nosepiece No. M96028 when using the Marson brand Big Daddy® or Big Daddy II hand tool.

KLICK-FAST RIVETS conform to IFI-130 (inch) and IFI-505 (metric). Millimeters (mm) and newtons (N) are in green.

**Also available in packaged quantities.

Automotive/Special Application Rivets

Trim Rivets

AFS Description	Bulk Part No.**	Grip Range	Description	Materials Body/Mandrel	Rivet Dia. Nom	Flange Dia. Nom.	Hole Dia. Range	500 Pack No.
ABN4-3A	M50261*	.126-.187	Trim Moulding Rivet	Alum/Alum	.125	.208	.129-.133	M40261
ABN4-4A	M50262*	.188-.250	Long Trim Moulding Rivet	Alum/Alum	.125	.208	.129-.133	M40262
SSBN4-3	M50516*	.126-.187	Trim Moulding Rivet w/SS Body	SS/Steel	.125	.208	.129-.133	M40516

*Use 39112 Trim Clip Rivet Nosepieces with HP-2 or HP-3 to form trim clip studs with 50261; 50262; 50516 rivets.

Klik-Split® Window & Door Rivets†

								50 Pack No.
—	M52371	.032-.140	Window Regulator Rivet	Alum/Steel	.250	.500	.257-.261	M42371
—	M52372	.090-.115	Outside Door Handle Rivet with recessed head	Alum/Steel	.250	.500	.257-.261	M42372
—	M52373	.110-.177	Door Handle Rivet with recessed head and zinc coated mandrel	Alum/Steel	.250	.500	.257-.261	M42373
—	M52374	.140-.187	Window Regulator Rivet with yellow zinc coated mandrel	Alum/Steel	.250	.500	.257-.261	M42374
—	M52375	.090-.115	Blk. Anodized Door Handle Rivet	Alum/Steel	.250	.500	.257-.261	M42375
—	M50376	.520-.620	Glass Stop Rivet	Alum/Steel	.250	.500	.257-.261	M42376



† Requires nosepiece No. M96028 when using the Marson brand Big Daddy® or Big Daddy® II hand tool.

Miscellaneous Rivets


								50 Pack No.
—	M53150	.250-.375	Bumper Fascia Rivet large flange black	Steel/Steel	.187	.625	.192-.196	M43150
—	M53353	.125-.187	Trunk Lock Swivel Emblem Rivet sealed end, countersunk head	Alum/Steel	.156	.312	.160-.164	M43353
								100 Pack No.
—	M53295	.125-.187	Rear Window Gasket Rivet	Alum/Steel	.125	.325	.129-.130	M43295
—	M53181	.125-.250	Bumper Fascia Rivet w/yellow zinc coated mandrel	Steel/Steel	.250	.500	.257-.261	M43181

**Also available in packaged quantities.


Klik-Lock™ Rivets




1 After drilling hole to proper diameter, rivet is placed into hole and rivet setting tool is placed over mandrel.




2 Actuating tool starts mandrel into rivet body, pulling work material together and expanding body on the blind side.



3 A solid circle lock is created between the body and mandrel creating a weather resistant assembly that virtually eliminates pin pushout.



4 After the mandrel is broken, the mandrel is flush with the rivet body removing the need for grinding.



5 The expansion of the body tightly fills the hole creating a weather-resistant joint.

AFS Description	Bulk Part No.**	Grip Range Inch (mm)	A Rivet Dia. Inch (mm)	Required Hole Size Inch (mm)	B Head Dia. Inch (mm)	C Head Height Max. Inch (mm)	D Body Length Max. Inch (mm)	E Overall Length Max. Inch (mm)	F Length Max. Inch (mm)	Average Shear Strength lbs. (newtons)	Average Tensile Strength lbs. (newtons)
-----------------	-----------------	-------------------------	------------------------	------------------------------	-----------------------	------------------------------	------------------------------	---------------------------------	-------------------------	---------------------------------------	---

Steel Rivet • Steel Mandrel • Buttonhead

SB6-4KL	M50807	.062-.270 1.57-6.85	.188 4.8	.191-.201 4.9-5.10	.385 9.77	.085 2.15	.415 10.45	.675 15.87	1.00 25.40	1450 6499	1200 5379
SB6-7KL	M50808	.214-.437 5.43-11.09					.572 14.52	.825 20.95	1.00 25.40		
SB6-EKL	M50809	.062-.437 1.57-11.09					.572 14.52	.950 24.13	1.00 25.40		
SB8-6KL	M50810	.080-.375 2.03-9.52	.257 6.5	.261-.272 6.6-6.9	.525 13.33	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	2750 12326	2200 9861
SB8-10KL	M50811	.350-.625 8.89-15.75					.810 20.57	1.220 30.98	1.00 25.40		
SB8-EKL	M50812	.080-.625 2.03-15.87					.810 20.57	1.405 35.68	1.00 25.40		

Large Flange

SBL6-4KL	M50813	.062-.270 1.57-6.85	.188 4.8	.191-.201 4.9-5.1	.500 12.70	.085 2.15	.415 10.45	.675 15.87	1.00 25.40	1450 6499	1200 5379
SBL6-EKL	M50814	.062-.437 1.57-11.09					.572 14.52	.950 24.13	1.00 25.40		
SBL8-6KL	M50815	.080-.375 2.03-9.52	.257 6.5	.261-.272 6.6-6.9	.588 14.93	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	2750 12326	2200 9861

100° Countersunk

SC6-6KL	M50816	.125-.331 3.17-8.40	.188 4.8	.191-.201 4.9-5.1	.345 8.8	.070 1.8	.486 12.34	.762 19.35	1.00 25.40	1450 6499	1200 5379
SC6-9KL	M50818	.305-.500 7.74-12.70					.653 16.58	.929 23.59	1.00 25.40		
SC8-8KL	M50819	.160-.475 4.06-12.06	.257 6.5	.261-.272 6.6-6.9	.405 10.3	.079 2.0	.660 16.76	1.059 26.89	1.00 25.40	2750 12326	2200 9861
SC8-12KL	M50820	.415-.725 10.54-18.41					.910 23.11	1.309 33.24	1.00 25.40		

**Also available in packaged quantities.

AFS Description	Bulk Part No.**	Grip Range Inch (mm)	A Rivet Dia. Inch (mm)	Required Hole Size Inch (mm)	B Head Dia. Inch (mm)	C Head Height Max. Inch (mm)	D Body Length Max. Inch (mm)	E Overall Length Max. (mm)	F Length Max. Inch (mm)	Average Shear Strength lbs. (newtons)	Average Tensile Strength lbs. (newtons)
-----------------	-----------------	-------------------------	------------------------	------------------------------	-----------------------	------------------------------	------------------------------	----------------------------	-------------------------	---------------------------------------	---

Stainless Rivet • Stainless Mandrel • Buttonhead

SSB6-4SKL	M50833	.062-.270 1.57-6.85	.188 4.8	.191-.201 4.9-5.1	.385 9.8	.085 2.15	.415 10.54	.625 17.14	1.00 25.40	1400 6275	1000 4482
SSB6-7SKL	M50834	.214-.437 5.43-11.09					.572 14.52	.825 20.95	1.00 25.40		
SSB6-ESKL	M50835	.062-.437 1.57-11.09					.572 14.52	.950 24.13	1.00 25.40		
SSB8-6SKL	M50836	.080-.375 2.03-9.52	.257 6.5	.261-.272 6.6-6.9	.525 13.3	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	2750 11206	2200 8964
SSB8-10SKL	M50837	.350-.625 8.89-15.87					.810 20.57	1.220 30.98	1.00 25.40		

100° Countersunk

SSC6-6SKL	M50838	.125-.331 3.17-8.40	.188 4.8	.191-.201 4.9-5.1	.345 8.8	.070 1.8	.486 12.34	.762 19.35	1.00 25.40	1400 6275	1000 4482
SSC8-8SKL	M50839	.160-.475 4.06-12.06	.257 6.5	.261-.272 6.6-6.9	.405 10.3	.079 2.0	.560 14.62	1.059 26.89	1.00 25.40	2500 11206	2000 8964

Aluminum Rivet • Aluminum Mandrel • Buttonhead

AB6-4AKL	M50821	.062-.270 1.57-6.85	.188 4.8	.191-.201 4.9-5.1	.385 9.8	.085 2.15	.415 10.54	.675 15.87	1.00 25.40	700 3138	500 2241
AB6-7AKL	M50822	.214-.437 5.43-11.09					.572 14.52	.825 20.95	1.00 25.40		
AB6-AEKL	M50823	.062-.437 1.57-11.09					.572 14.52	.950 24.13	1.00 25.40		
AB8-6AKL	M50824	.080-.375 2.03-9.52	.257 6.5	.261-.272 6.6-6.9	.525 13.33	.117 2.97	.560 14.62	.970 24.63	1.00 25.40	1300 5827	890 3989
AB8-10AKL	M50825	.350-.625 8.89-15.87					.810 20.57	1.220 30.98	1.00 25.40		
AB8-AEKL	M50826	.080-.625 2.03-15.87					.810 20.57	1.405 35.56	1.00 25.40		

Aluminum/Large Flange

ABL6-4AKL	M50827	.062-.270 1.57-6.85	.188 4.8	.191-.201 4.9-5.1	.500 12.7	.085 2.15	.415 10.45	.675 15.87	1.00 25.40	700 3138	500 2241
ABL6-7AKL	M50828	.214-.437 5.43-11.09					.572 14.52	.825 20.95	1.00 25.40		

Aluminum/100° Countersunk

AC6-6AKL	M50829	.125-.331 3.17-8.40	.188 4.8	.191-.201 4.9-5.1	.345 8.8	.070 1.8	.486 12.34	.762 19.35	1.00 25.40	700 3138	500 2241
AC6-9AKL	M50830	.305-.500 7.74-12.70					.653 16.58	.929 23.59	1.00 25.40		
AC8-8AKL	M50831	.160-.475 4.06-12.06	.257 6.5	.261-.272 6.6-6.9	.405 10.3	.079 2.0	.660 16.76	1.059 26.89	1.00 25.40	1300 5827	890 3989
AC8-12AKL	M50832	.415-.725 10.54-18.41					.910 23.11	1.309 33.24	1.00 25.40		

Pin Retention Values

		Steel lbs.	Aluminum lbs.	Stainless Steel lbs.
3/16"	Pin Retention	300	50	125
1/4"	Pin Retention	500	100	250



When setting Marson brand Klik-Lock rivets, no special nosepiece is required.



Material and Finish

Material	Sleeve	Pin	Sleeve Finish	Pin Finish
Steel	Low	Medium	Zinc Plated	Zinc Plated Clear Trivalent Chromate
	Carbon Steel	Carbon Steel	Clear Chromate	Zinc Plated Clear Trivalent Chromate
Aluminum	5056	7075	Clear Chromate	Clear Trivalent Chromate
Stainless	302	305/304	Passivated	Dry Lubricated

Millimeters (mm) and newtons (N) are in green.

**Also available in packaged quantities.

Plastic Rivets



Plastic rivet before and after set.


Klik-Lok™ Plastic Rivets • Nylon Body ST801HS • Delrin 500 Mandrel

Marson brand Klik-Lok Plastic Rivets are the same precision-molded all-nylon rivets used by domestic auto manufacturers, both for original equipment and replacement parts. In addition, Klik-Lok Plastic Rivets are ideal for non-conductive and non-corrosive environments. Klik-Lok Plastic Rivets fasten plastic to plastic, plastic to metal and plastic to fiberglass. As they set, three "legs" form to securely lock the components in place and prevent pullout.

Diagram Reference	100-Pack Part No.*	Grip Range		D Rivet Dia.		Hole Size		H Head Dia.		E Head Height		Rivet Length		Typical Ultimate Strength (lbs.)		
		Inch	(mm)	Nom. Inch		Inch	(mm)	Inch	(mm)	Inch	(mm)	Max. Inch	(mm)	Shear (N)	Tensile (N)	
A	M48286	.236 - .413	6.0 - 10.5	.154		.156	4	.315	8	.098	2.5	1.024	20	40	178	82 365
B	M48305	.059 - .177	1.5 - 4.5	.195		.197	5	.472	12	.130	3.3	.728	18.5	68	302	120 534
C	M48306	.118 - .236	3.0 - 6.0	.195		.197	5	.472	12	.071	1.8	.787	20	68	302	120 534
D	M48307	.118 - .177	3.0 - 4.5	.195		.197	5	.472	12	.071	1.8	.787	20	68	302	120 534
E	M48308	.236 - .394	6.0 - 10.0	.195		.197	5	.472	12	.071	1.8	.984	25	68	302	120 534
F	M48309	.118 - .157	3.0 - 4.0	.195		.197	5	.354	9	.071	1.8	.650	16.5	68	302	120 534
G	M48330	.157 - .335	4.0 - 8.5	.234		.236	6.0	.512	13	.098	2.5	1.102	28	110	489	181 805
H	M48349	.157 - .236	4.0 - 6.0	.246		.250	6.3	.669	17	.098	2.5	.709	18	121	538	194 863
I	M48350	.157 - .394	4.0 - 10.0	.246		.250	6.3	.669	17	.098	2.5	1.102	28	121	538	194 863
J	M48351	.157 - .394	4.0 - 10.0	.246		.250	6.3	.512	13	.098	2.5	1.102	28	121	538	194 863
K	M48353	.028 - .193	.7 - 5.0	.246		.250	6.3	.670	17	.098	2.5	.682	17.3	121	538	194 863
L	M48354	.028 - .178	.7 - 4.5	.246		.250	6.3	.670	17	.098	2.5	.682	17.3	121	538	194 863
M	M48385	.098 - .197	2.5 - 5.0	.258		.260	6.6	.512	13	.098	2.5	.787	20	137	609	219 974
N	M48386	.098 - .197	2.5 - 5.0	.258		.260	6.6	.709	18	.098	2.5	.787	20	137	609	219 974

* Also available in bulk 2,000/ctn and visual boxes, 20/pkg.

Actual Size Rivets/Flanges When ordering, match diagram reference letter with those in above chart.



Klik-Lok™ Plastic Rivet Setter/M48000

This plastic rivet setter delivers the extra-long pulling stroke needed to set plastic rivets. Its all-steel construction and full-size handles make for smooth easy operation. The tool is packaged in a reusable, heavy-duty vinyl pouch. Weight: .6 lb.



Klik-Lok™ Plastic Rivet Kit/M48001

You'll be all set for the next job that requires plastic rivet fastening with this kit. The kit includes the M48000 Plastic Rivet Setter and a 20-pack each of our four most popular rivet sizes: No. M58106, M58108, M58149 and M58150. A reclosable carton provides storage for rivets and tool. Weight: 1.5 lbs.

Klik-Lok™ KL-2 Plastic Rivet Setter/M48005

This long-reach tool is just what today's professional needs for hard-to-reach spots, especially in automotive applications such as flexible bumpers, wheel wells, license plate brackets and bumper reinforcements. In addition to the tool's long reach, it offers one-stroke setting and a universal nosepiece that sets all plastic rivets. The tool is packaged in a reusable, heavy-duty vinyl pouch. Weight: .75 lb.



Professional Plastic Rivet Kit/M48006

This kit includes the versatile KL-2 Plastic Rivet Setter, plus a 20-pack each of our four most popular rivet sizes: No. M58106, M58108, M58149 and M58150. A reclosable carton provides storage for rivets and tool. Weight: 1.5 lbs.

Hand Rivet Tools



HP-2®/M39000

The HP-2 is the number one selling hand rivet tool in the industry. Known and trusted for durability, quality and performance, the HP-2 is often copied but never duplicated. Its square shoulder fulcrum pin of cold-formed heat-treated steel prevents pin rotation that can elongate the engaging holes and cause premature tool failure in imitation tools. Other quality features include: precision die-cast, high-strength aluminum alloy body; drop-forged carbon steel upper handle; and thick, cushion-molded vinyl grips for comfort. The HP-2 sets up to 3/16" steel rivets and comes with four mounted nosepieces (3/32", 1/8", 5/32" and 3/16") and a service wrench. Refer to the Riveter Capacity Chart on page 19 for specific capabilities. Weight: 1.2 lbs.

HP-3®/M39002

Our newest tool offers long, ergonomically designed handles to increase leverage. The tool is spring loaded to secure the rivet in the nosepiece while the tool is in any position. The HP-3 offers powerful riveting capacity with 4 standard nosepieces to set 3/32", 1/8" and 5/32" in all alloys and up to 3/16" in steel. It features a drop-forged steel handle with heat-treated aluminum body with steel insert, high quality powder coated finish, special alloy steel fulcrum pin with anti-wearing design, and durable jaws and jaw case. Weight: 1.2 lbs.



NEW

Klik-Turn™ SP-1/M39005

The SP-1 swivel head hand-held rivet tool features a patented positive-ratchet locking feature which will allow the swivel head section of the tool to turn 360° and hold in place in any of the forty-plus positions. The high-strength steel body and cast aluminum head complement this new design in a swivel head riveting tool. The SP-1 also includes built-in threaded nosepiece storage holes and a service wrench. The SP-1 sets up to 3/16" steel rivets. Weight: 1.2 lbs.



200 Kit™/M39001

The deluxe hand riveter kit includes the HP-2 and 200 assorted Klik-Fast rivets: 40 each SB4-2, SB4-4, AB4-2A; 25 each SC4-4, AB6-2. The molded plastic case houses and protects the tool and rivets. Weight: 4 lbs.

Stainless Steel Kit/M39003

This kit is the same as our M39001, but contains 200 assorted Klik-Fast stainless steel rivets: 40 each SSB4-2S, SSB4-3S, SSB4-4S, SSBL4-2S, SSBL4-4S. Weight: 4 lbs.

Big Daddy®/M39031

The Big Daddy is the most versatile and powerful Marson brand hand riveter, taking the hard work out of setting large diameter blind rivets. Its extra-long handles provide excellent leverage and permit working a foot beyond natural reach. Other features include a patented bearing design, self-adjusting two-piece jaws and single-unit body construction with a steel insert to provide stronger threads for the nosepieces included. In addition, the Big Daddy features a double-gear reduction system which easily sets from 1/8" to 1/4" diameter Klik-Fast rivets in all alloys, including 1/4" Klik-Split® and 3/16" and 1/4" Klik-Lock™ rivets. And a one-piece collet case eliminates the need to adjust the tool when changing rivet diameters. The Big Daddy model # M39031 comes with 5/32", 3/16" and 1/4" nosepieces which are stored in the body. Weight: 3.75 lbs.



Big Daddy/M39035

This is the same tool as M39010, but comes with M39009 attached, extending the tool's reach by an additional 2 1/2". Weight: 4 lbs.



Big Daddy/M39010

This is the same tool as M39031, but comes with 3/16", 1/4" and special 1/4" Klik-Split rivet nosepieces. Weight: 3.75 lbs.

Big Daddy II/M39032

With all the features of the Big Daddy, Big Daddy II includes a built-in mandrel collection receptacle; just remove the end cap on the bottom handle to discard the spent mandrels.

Big Daddy Conversion Kit 3 Jaw Set Up/M96050

Converting to a three-jaw set adds additional gripping power and extends jaw life.

Big Daddy Extended Nosepiece Kit/M39009

Install kit to add an additional 2-1/2" to any Big Daddy Tool. Weight: .25 lb.



Hand Rivet Tool Capacity Chart

	Steel					All Aluminum					Aluminum Steel					Stainless					Mono-bolt®*		"T" Rivets	
	3/32"	1/8"	5/32"	3/16"	1/4"	3/32"	1/8"	5/32"	3/16"	1/4"	3/32"	1/8"	5/32"	3/16"	1/4"	3/32"	1/8"	5/32"	3/16"	1/4"	3/16"	1/4"	3/16"	1/4"
HP-2/M39000	•	•	•	•		•	•	•	•		•	•	•	•		•	•	•						
HP-3/M39002	•	•	•	•		•	•	•	•		•	•	•	•		•	•	•						
SP-1/M39005	•	•	•	•		•	•	•	•		•	•	•	•		•	•	•						
BIG DADDY (All)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Hand Rivet Tools — Standard & Special Nosepieces

	Sizes					Monobolt®*		T-Rivet Sizes	
	3/32"	1/8"	5/32"	3/16"	1/4"	3/16"	1/4"	3/16"	1/4"
HP-2/M39000	M39131	M39128	M39130	M39129					
HP-3/M39002	M39131	M39128	M39130	M39129					
SP-1/M39005	M39160	M39161	M39162	M39163					
BIG DADDY (All)		M96024	M96025	M96026	M96027	M96031	M96030	M96029	M96028

* When setting Marson band Klik-Lock rivets, no special nosepiece is required.

Air/Hydraulic Tools

These next-generation, professional-series air/hydraulic riveters are designed to be light weight and well-balanced. Both are engineered to maximize stroke and pull force with a 3-jaw set. For added convenience, you can direct connect or use the attached swivel. Each tool is supplied with nosepieces to set rivets in all alloys, and comes complete with adjustment service wrenches, hydraulic fluid, fluid applicator, spare jaws, and a removable swivel air connection line with an air OFF/ON valve built in. An adjustable vacuum system control allows you to control the force of air needed to hold the rivet in place. Or, you may operate with the vacuum system turned off. Recommended air pressure is 70-95 PSI.



NEW

MP-3V/M39045

Stroke: 3/4"

Pulling Force: 1,800 lbs.

Capacity: 3/32" – 3/16", all alloys

Weight: 2.9 lbs.



NEW

MP-4V/M39048

Stroke: 1"

Pulling Force: 3,420 lbs.

Capacity: 5/32" – 1/4", all alloys, 1/4" monobolt nosepiece included

Weight: 3.7 lbs.

Each of these proven, professional tools features a one-piece molded frame and front swivel air inlet for maximum operator comfort and durability. An external vacuum adjustment offers convenient air flow control for rivet placement and mandrel disposal. This allows the operator to install rivets in any orientation using one hand, and freeing up the other for assembly. Spent mandrels are conveniently collected in the bottle for disposal, encouraging a safer, clean work environment. Tools come complete with oil, replacement jaws, and nosepieces. Recommended air pressure: 85-95 psi.



302-E/M39062

Stroke: .812"

Pulling Force: 2,000 lbs.

Capacity: 3/32" – 3/16" diameter in all alloys and up to 1/4" in aluminum/steel combinations.

Weight: 4 lbs.



304-E/M39064

Stroke: 1"

Pulling Force: 4,200 lbs.

Capacity: 3/16" to 1/4" all alloys including structural rivets

Also included are 3/16" and 1/4" Monobolt® & Magna-lok assemblies.

Weight: 5.5 lbs.



Extended head accessory for 302-E and 304-E

Tool	Description	Part Number
302-E/M39062	5" Extension Head	M88082
302-E/M39062	8" Extension Head	M88086
304-E/M39064	5" Extension Head	M88220-39
304-E/M39064	5" Extension Head	M723358

171 New Style

Air/Hydraulic Rivet Tools – Standard & Special Nosepieces

	$\frac{3}{32}$ "	$\frac{1}{8}$ "	Standard $\frac{5}{32}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "	T-Rivets / Klik-Split® $\frac{1}{4}$ "	Monobolt®** $\frac{3}{16}$ "	$\frac{1}{4}$ "
MP-3V/M39045	M95200	M95201	M95202	M95203				
MP-4V/M39048			M95300	M95301	M95302		M95299	M95303
302-E/M39062	M717006	M717001	M717002	M717003	M717005			
304-E/M39064				M88220-1	M88220-79	M88220-83	M88220-85	M88220-84

*For Monobolt® structural rivets, the noted special nosepiece is required. For Marson brand Klik-Lock® structural rivets, no special insert is required.

Air/Hydraulic Rivet Tools – Capacity Chart

	Steel					All Aluminum					Aluminum Steel					Stainless					Struc- tural*		"T" Rivets	
	$\frac{3}{32}$ "	$\frac{1}{8}$ "	$\frac{5}{32}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "	$\frac{3}{32}$ "	$\frac{1}{8}$ "	$\frac{5}{32}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "	$\frac{3}{32}$ "	$\frac{1}{8}$ "	$\frac{5}{32}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "	$\frac{3}{32}$ "	$\frac{1}{8}$ "	$\frac{5}{32}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "	$\frac{3}{16}$ "	$\frac{1}{4}$ "
MP-3V/M39045	•	•	•	•		•	•	•	•		•	•	•	•		•	•	•	•					
MP-4V/M39048			•	•	•			•	•	•			•	•	•			•	•	•	•	•		
302-E/M39062	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•					
304-E/M39064				•	•				•	•				•	•			•	•	•	•	•	•	•


*For Monobolt® structural rivets, the noted special nosepiece is required. For Marson brand Klik-Lock® structural rivets, no special insert is required.

Air/Hydraulic Rivet Tools – Dimensions

Tool	A	B	C	D	E	F	G	WT
MP-3V/M39045	10.000"	3.500"	1.500"	3.500"	6.500"	.750"	2.750"	2.9 lbs.
MP-4V/M39048	12.000"	5.500"	2.000"	4.500"	7.000"	.750"	3.500"	3.7 lbs.
302-E/M39062	11.125"	5.000"	2.375"	4.500"	13.000"	.828"	2.500"	4 lbs.
304-E/M39064	13.125"	6.000"	2.375"	5.250"	13.000"	.938"	2.500"	5.5 lbs.

Air/Hydraulic Rivet Tools – Specifications

Tool	Work Force	Stroke
MP-3V/M39045	70-95 psi 1,800 lbs./8007 n	.750 19 mm
MP-4V/M39048	70-95 psi 3,420 lbs./15,213 n	1.000 25.4 mm
302-E/M39062	85-95 psi 2,000 lbs./8,896 n	.812" 21 mm
304-E/M39064	85-95 psi 4,200 lbs./18,682 n	1.000" 25.4 mm



Marson Rivet Nuts

More styles, sizes and tools to fit your application needs.

Marson Rivet Nuts deliver low cost permanent thread placement in thin material while providing at least six full thread turns per application install. Easy Installation can be completed by one operator with minimum training. Blind side access is not required when installing Marson Rivet Nuts. Ideal for painted surfaces, Marson Rivet Nuts help increase production and reduce rework by eliminating the surface damage than can occur with other fastening methods.

4 Easy Steps to Complete Installation and Application

- 1** Thread rivet nut onto tool mandrel and insert into hole.
- 2** Actuate tool to properly set fastener into material.
- 3** Complete your fastening operation with a bolt or screw with the proper thread.
- 4** The positive riveting action of the Klik Rivet Nut will provide a permanent thread. As threads are tightened, so are rivet nut and application.

Rivet Nuts can be used to fasten multiple sheets as well as single sheets



General Information — Rivet Nuts

Rivet Styles

Features/Benefits

Materials Available

MRN Series
(p. 24)



Rivet Nut, Flathead Flange (thick wall) for applications that require heavy push out loads (recommend spin-pull tool)

Steel, Aluminum

MPN Series
(p. 25)



Poly-Nut Rivet Nut has very small flange, lowest profile for near counter sink application

Steel, Aluminum

MTS Series
(p. 25)



Thread-Sert has small flange, 360 degree swaging action in the hole and no maximum grip range

Steel, Aluminum

MLR Series
(p. 26)



Large Flange Ribbed Rivet Nut provides increased turn-out resistance vs conventional rivet nut and large flange for improved push out performance

Steel, Aluminum

MLC Series
(p. 27)



Large Flange Ribbed Rivet Nut with Closed End for thread seal

Steel, Aluminum

MSR Series
(p. 28)



Small Flange low profile Ribbed Rivet Nut virtually flush install with increased turn-out resistance vs conventional low profile Poly-Nut

Steel, Aluminum

MSC Series
(p. 29)



Small Flange low profile Ribbed Rivet Nut with Closed End for thread seal

Steel, Aluminum

MHN Series
(p. 30)



Large Flange Half Hex Rivet Nut for hex hole to provide exceptional turn-out resistance

Steel

MQN Series
(p. 31)



Quad-Leg Rivet Nut used for light duty thin or soft/ brittle material – will accommodate slightly oversized hole with large back side footprint

Steel

MXN Series
(p. 31)



Large Flange Cross Bulb Rivet Nut large grip range with pre-bulb and 4 slots cut to provide large blindside footprint for greater pull out strength in thin sheet metal and plastics.

Steel

MET Series
(p. 32)



External Thread Stud Rivet Nut allows for component mounting and mate nut

Steel

MNN Series
(p. 33)



Neoprene Insert with pre-molded brass nut for quick fastening in vibration and moisture resistant applications

Neoprene


All finishes are RoHS compliant.

MRN Series Flathead Rivet Nuts

Available in Steel-Zinc Plated or Aluminum

MRN Series Flathead Rivet Nut (Thick Wall)

MRN — Rivet Nut, Flathead Flange provides the most bearing surface for applications that require heavy push out loads and high torque for use in metal, fiberglass and rigid plastics too thin for tapped holes. Spin/Pull tool is recommended although smaller thread sizes can utilize a manual tool.



MRN Series Flathead Rivet Nut

Thread Size	Grip Range		Steel *Bulk Part #	Aluminum *Bulk Part #	A Body Length ±.015"	B Head Dia. ±.015"	C Head Height (nom.)	D Body Dia. Max.	Hole Size		Drill Size
	Min.	Max.							Min.	Max.	
6-32	.010	.075	M57110	M57210	.438	.325	.032	.189	.189	.193	#12
8-32	.010	.075	M57120	M57220	.438	.357	.032	.221	.221	.226	#2
8-32	.075	.120	M57121	M57221	.500	.357	.032	.221	.221	.226	#2
10-24	.010	.080	M57130	M57230	.531	.406	.038	.250	.250	.254	1/4
10-24	.080	.130	M57132	M57232	.594	.406	.038	.250	.250	.254	1/4
10-32	.010	.080	M57140	M57240	.531	.406	.038	.250	.250	.254	1/4
10-32	.080	.130	M57142	M57242	.594	.406	.038	.250	.250	.254	1/4
1/4-20	.020	.080	M57150	M57250	.625	.475	.058	.332	.332	.338	Q (.332)
1/4-20	.080	.140	M57152	M57252	.687	.475	.058	.332	.332	.338	Q (.332)
1/4-20	.140	.200	M57154	M57254	.750	.475	.058	.332	.332	.338	Q (.332)
5/16-18	.030	.125	M57171	M57271	.750	.665	.062	.413	.413	.423	Z (.423)
5/16-18	.125	.200	M57174	M57274	.875	.665	.062	.413	.413	.423	Z (.423)
3/8-16	.030	.115	M57181	M57281	.844	.781	.088	.490	.490	.500	1/2
3/8-16	.115	.200	M57184	M57284	.938	.781	.088	.490	.490	.500	1/2


* Also available in small packaged quantities.
Inch sizes are class 2B thread.
Metric sizes are class 6H thread.

MPN Series Poly-Rivet Nut

Available in Steel-Zinc Plated or Aluminum

MPN Series Lowest Profile Poly-Rivet Nut

MPN — Poly-Nut Rivet Nut has very small flange, lowest profile for near flush installation. Eliminates additional operations of countersinking or dimpling of the parent material. May install with all pneumatic and manual Rivet Nut tools.



MPN Series Poly Rivet Nut


Thread Size	Grip Range Min. - Max.	Steel *Bulk Part #	Aluminum *Bulk Part #	A Body Length ±.015 ± 0.38 mm	B Head Dia. ± .015 ± 0.38 mm	C Head Height ± .005 ± .0127 mm	D Body Dia. +0 -.005 to -0.127 mm	Hole Size Min. - Max.	Drill Size
6-32	.020-.080	M57415	M57510	.410	.287	.017	.249	.250-.254	1/4
8-32	.020-.080	M57425	M57520	.410	.287	.017	.249	.250-.254	1/4
10-24	.020-.130	M57435	M57530	.465	.320	.020	.280	.281-.285	9/32
10-32	.020-.130	M57445	M57540	.465	.320	.020	.280	.281-.285	9/32
1/4-20	.030-.165	M57455	M57550	.591	.415	.020	.374	.375-.379	3/8
5/16-18	.030-.165	M57475	M57575	.720	.540	.024	.499	.500-.504	1/2
3/8-16	.030-.165	M57485	M57585	.720	.540	.024	.499	.500-.504	1/2
4 mm	.50-2.03	M57407	N/A	10.41	7.29	0.43	6.32	6.35-6.45	6.35
5 mm	.50-3.30	M57409	N/A	11.81	8.13	.61	7.11	7.14-7.23	7.14
6 mm	.76-4.19	M57411	N/A	15.01	10.54	.61	9.50	9.52-9.62	9.52
8 mm	.76-4.19	M57413	N/A	18.29	13.72	.61	12.67	12.7-12.8	12.7
10 mm	.76-4.19	M57414	N/A	18.29	13.72	.61	12.67	12.7-12.8	12.7

* Also available in small packaged quantities.
Inch sizes are class 2B thread. Metric sizes are class 6H thread.

MTS Series Thread-Serts

Available in Steel-Zinc Plated or Aluminum

MTS — Thread-Sert has small flange and 360 degree swaging action as the rivet nut expands inside the hole. Provides high resistance to torque out with minimal backside protrusion. Can be installed in blind hole with unlimited maximum grip range. May install with all pneumatic and manual Rivet Nut tools.



MTS Series Thread Sert


Thread Size	Steel *Bulk Part #	Aluminum *Bulk Part #	A** Body Length ±.005"	B Head Dia. ±.005"	D** Body Dia. ±.002"	Material Thickness .0937-.1562		Material Thickness .1562- Infinity	
						Hole Size	Drill Size	Hole Size	Drill Size
6-32	M57810	M57910	.375	.250	.215	.221	# 2	.234	A (.234)
8-32	M57820	M57920	.375	.282	.246	.250	1/4	.261	G (.261)
10-24	M57830	M57930	.375	.314	.277	.281	9/32	.290	L (.290)
10-32	M57840	M57940	.375	.314	.277	.281	9/32	.290	L (.290)
1/4-20	M57850	M57950	.510	.408	.372	.391	3/8	.376	25/64
5/16-18	M57871	M57971	.615	.537	.496	.500	1/2	.516	33/64
3/8-16	M57881	M57981	.740	.600	.559	.562	9/16	.578	37/64

* Also available in small packaged quantities. ** A and D dimensions are prior to setting
Inch sizes are class 2B thread. Metric sizes are class 6H thread.

MLR Series Large Flange Ribbed Low-Profile Rivet Nuts

Available in Steel-Zinc Plated or Aluminum

MLR — Large Flange Ribbed Rivet Nut feature ribbed external body for increased torque out resistance vs conventional rivet nut. Large flange offers improved push out performance. Overall MLR offers the best/highest strength levels. May install with all pneumatic and manual Rivet Nut tools.



MLR Series Large Flange Ribbed Low-Profile Rivet Nut


Thread Size	Grip Range Min-Max	Steel *Bulk Part #	Aluminum *Bulk Part #	A Body Length ±.015" ± 0.38 mm	B Head Dia. ±.010" ± 0.254 mm	C Head Height ±.003" ± 0.76 mm	D Body Dia. Max	Hole Size Min-Max	Drill Size
6-32	.020 - .080	M57310	M57610	.420	.390	.030	.265	.265 - .271	17/64
6-32	.080 - .130	M57312	M57612	.470	.390	.030	.265	.265 - .271	17/64
8-32	.020 - .080	M57320	M57620	.420	.390	.030	.265	.265 - .271	17/64
8-32	.080 - .130	M57321	M57621	.470	.390	.030	.265	.296 - .302	17/64
10-24	.020 - .130	M57330	M57630	.475	.415	.030	.296	.296 - .302	19/64
10-24	.130 - .225	M57332	M57632	.585	.415	.030	.296	.296 - .302	19/64
10-32	.020 - .130	M57340	M57640	.475	.415	.030	.296	.296 - .302	19/64
10-32	.130 - .225	M57342	M57642	.585	.415	.030	.296	.296 - .302	19/64
1/4-20	.027 - .165	M57350	M57650	.580	.500	.030	.390	.390 - .396	25/64
1/4-20	.165 - .260	M57354	M57654	.680	.500	.030	.390	.390 - .396	25/64
1/4-28	.027 - .165	M57358	M57658	.580	.500	.030	.390	.390 - .396	25/64
1/4-28	.165 - .260	M57359	M57659	.680	.500	.030	.390	.390 - .396	25/64
5/16-18	.027 - .150	M57371	M57671	.690	.685	.035	.530	.530 - .536	17/32
5/16-18	.150 - .312	M57374	M57674	.805	.685	.035	.530	.530 - .536	17/32
5/16-24	.027 - .150	M57378	M57678	.690	.685	.035	.530	.530 - .536	17/32
5/16-24	.150 - .312	M57379	M57679	.805	.685	.035	.530	.530 - .536	17/32
3/8-16	.027 - .150	M57381	M57681	.690	.865	.035	.530	.530 - .536	17/32
3/8-16	.150 - .312	M57382	M57682	.805	.865	.035	.530	.530 - .536	17/32
3/8-24	.027 - .150	M57395	M57695	.690	.685	.035	.530	.530 - .536	17/32
3/8-24	.150 - .312	M57396	M57696	.805	.685	.035	.530	.530 - .536	17/32
M4x.07	.5 - 2.0	M57360	M57660	10.67	9.91	.76	6.73	6.75 + .15	6.75
M4x.07	2.0 - 3.3	M57365	M57665	11.94	9.91	.76	6.73	6.75 + .15	6.75
M5x0.8	.5 - 3.3	M57385	M57684	12.07	10.54	.76	7.52	7.6 + .15	7.6
M5x0.8	3.3 - 5.7	M57384	M57685	14.86	10.54	.76	7.52	7.6 + .15	7.6
M6x1.0	.7 - 4.2	M57386	M57686	14.73	12.7	.76	9.91	10.0 + .15	10.0
M6x1.0	4.2 - 6.6	M57387	M57687	17.27	12.7	.76	9.91	10.0 + .15	10.0
M8x1.25	.7 - 3.8	M57388	M57688	17.53	17.4	.89	13.46	13.5 + .15	13.5
M8x1.25	3.8 - 7.9	M57389	M57689	20.45	17.4	.89	13.46	13.5 + .15	13.5
M10x1.5	.7 - 3.8	M57390	M57690	17.53	17.4	.89	13.46	13.5 + .15	13.5
M10x1.5	3.8 - 7.9	M57391	M57691	20.45	17.4	.89	13.46	13.5 + .15	13.5

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
 Inch sizes are class 2B thread.
 Metric sizes are class 6H thread.

MLC Series Large Flange Closed End Ribbed Rivet Nuts

Available in Steel-Zinc Plated or Aluminum

MLC — Large Flange Ribbed Rivet Nut same as MLR with Closed End for complete thread seal. Use in moisture resistant applications. May install with all pneumatic and manual Rivet Nut tools.



MLC Series Large Flange Closed End Ribbed Rivet Nut

Thread Size	Grip Range Min-Max	Steel *Bulk Part #	Aluminum *Bulk Part #	A Body Length ±.015" ± 0.38 mm	B Head Dia. ±.010" ± 0.254 mm	C Head Height ±.003" ± 0.76 mm	D Body Dia. Max	Hole Size Min-Max	Drill Size
6-32	.020 - .080	M56810	M56910	.740	.390	.030	.265	.265 - .271	17/64
6-32	.080 - .130	M56812	M56912	.740	.390	.030	.265	.265 - .271	17/64
8-32	.020 - .080	M56820	M56920	.740	.390	.030	.265	.265 - .271	17/64
8-32	.080 - .130	M56821	M56921	.740	.390	.030	.265	.296 - .302	17/64
10-24	.020 - .130	M56830	M56930	.990	.415	.030	.296	.296 - .302	19/64
10-24	.130 - .225	M56832	M56932	.990	.415	.030	.296	.296 - .302	19/64
10-32	.020 - .130	M56840	M56940	.990	.415	.030	.296	.296 - .302	19/64
10-32	.130 - .225	M56842	M56942	.990	.415	.030	.296	.296 - .302	19/64
1/4-20	.027 - .165	M56850	M56950	1.190	.500	.030	.390	.390 - .396	25/64
1/4-20	.165 - .260	M56854	M56954	1.190	.500	.030	.390	.390 - .396	25/64
1/4-28	.027 - .165	M56858	M56958	1.190	.500	.030	.390	.390 - .396	25/64
1/4-28	.165 - .260	M56859	M56959	1.190	.500	.030	.390	.390 - .396	25/64
5/16-18	.027 - .150	M56871	M56971	1.390	.685	.035	.530	.530 - .536	17/32
5/16-18	.150 - .312	M56874	M56974	1.390	.685	.035	.530	.530 - .536	17/32
5/16-24	.027 - .150	M56878	M56978	1.390	.685	.035	.530	.530 - .536	17/32
5/16-24	.150 - .312	M56879	M56979	1.390	.685	.035	.530	.530 - .536	17/32
3/8-16	.027 - .150	M56881	M56981	1.390	.685	.035	.530	.530 - .536	11/16
3/8-16	.150 - .312	M56882	M56982	1.390	.685	.035	.530	.530 - .536	11/16
3/8-24	.027 - .150	M56895	M56995	1.390	.685	.035	.530	.530 - .536	11/16
3/8-24	.150 - .312	M56896	M56996	1.390	.685	.035	.530	.530 - .536	11/16
M4x.07	.5 - 2.0	M56860	M56960	18.8	9.91	.76	6.73	6.75 + .15	6.75
M4x.07	2.0 - 3.3	M56865	M56965	18.8	9.91	.76	6.73	6.75 + .15	6.75
M5x0.8	.5 - 3.3	M56884	M56984	25.15	10.54	.76	7.52	7.6 + .15	7.60
M5x0.8	3.3 - 5.7	M56885	M56985	25.15	10.54	.76	7.52	7.6 + .15	7.60
M6x1.0	.7 - 4.2	M56886	M56986	30.23	12.7	.76	9.91	10.0 + .15	10.00
M6x1.0	4.2 - 6.6	M56887	M56987	30.23	12.7	.76	9.91	10.0 + .15	10.00
M8x1.25	.7 - 3.8	M56888	M56988	35.31	17.4	.89	13.46	13.5 + .15	13.50
M8x1.25	3.8 - 7.9	M56889	M56989	35.31	17.4	.89	13.46	13.5 + .15	13.50
M10x1.5	.7 - 3.8	M56890	M56990	35.31	17.4	.89	13.46	13.5 + .15	13.50
M10x1.5	3.8 - 7.9	M56891	M56991	35.31	17.4	.89	13.46	13.5 + .15	13.50

Dimensions in green indicate millimeters (mm) *Also available in small packaged quantities.
 Inch sizes are class 2B thread.
 Metric sizes are class 6H thread.

MSR Series Small Flange Low Profile Ribbed Rivet Nuts

Available in Steel-Zinc Plated or Aluminum

MSR — Small Flange low profile Ribbed Rivet Nut virtually flush installation with ribbed external body for increased torque-out resistance vs conventional low profile Poly-Nut. May install with all pneumatic and manual Rivet Nut tools.



MSR Series Small Flange Low Profile Ribbed Rivet Nut


Thread Size	Grip Range Min-Max	Steel *Bulk Part #	Aluminum *Bulk Part #	A Body Length ±.015" ± 0.38 mm	B Head Dia. ±.010" ± 0.254 mm	C Head Height ±.003" ± 0.76 mm	D Body Dia. Max	Hole Size Min-Max	Drill Size Min-Max
6-32	.020 - .080	M56810	M56910	.420	.310	.019	.265	.265 - .271	17/64
6-32	.080 - .130	M56812	M56912	.470	.310	.019	.265	.265 - .271	17/64
8-32	.020 - .080	M56820	M56920	.420	.310	.019	.265	.265 - .271	17/64
8-32	.080 - .130	M56821	M56921	.470	.310	.019	.265	.296 - .302	17/64
10-24	.020 - .130	M56830	M56930	.475	.340	.019	.296	.296 - .302	19/64
10-24	.130 - .225	M56832	M56932	.585	.340	.019	.296	.296 - .302	19/64
10-32	.020 - .130	M56840	M56940	.475	.340	.019	.296	.296 - .302	19/64
10-32	.130 - .225	M56842	M56942	.585	.340	.019	.296	.296 - .302	19/64
1/4-20	.027 - .165	M56850	M56950	.580	.455	.022	.390	.390 - .396	25/64
1/4-20	.165 - .260	M56854	M56954	.680	.455	.022	.390	.390 - .396	25/64
1/4-28	.027 - .165	M56858	M56958	.580	.455	.022	.390	.390 - .396	25/64
1/4-28	.165 - .260	M56859	M56959	.680	.455	.022	.390	.390 - .396	25/64
5/16-18	.027 - .150	M56871	M56971	.690	.595	.022	.530	.530 - .536	17/32
5/16-18	.150 - .312	M56874	M56974	.805	.595	.022	.530	.530 - .536	17/32
5/16-24	.027 - .150	M56878	M56978	.690	.595	.022	.530	.530 - .536	17/32
5/16-24	.150 - .312	M56879	M56979	.805	.595	.022	.530	.530 - .536	17/32
3/8-16	.027 - .150	M56881	M56981	.690	.595	.022	.530	.530 - .536	17/32
3/8-16	.150 - .312	M56882	M56982	.805	.595	.022	.530	.530 - .536	17/32
3/8-24	.027 - .150	M56895	M56995	.690	.595	.022	.530	.530 - .536	17/32
3/8-24	.150 - .312	M56896	M56996	.805	.595	.022	.530	.530 - .536	17/32
M4x.07	.5 - 2.0	M56860	M56960	10.67	7.87	.48	6.73	6.75 + .15	6.75
M4x.07	2.0 - 3.3	M56865	M56965	11.94	7.87	.48	6.73	6.75 + .15	6.75
M5x0.8	.5 - 3.3	M56884	M56984	12.07	8.64	.48	7.52	7.6 + .15	7.60
M5x0.8	3.3 - 5.7	M56885	M56985	14.86	8.64	.48	7.52	7.6 + .15	7.60
M6x1.0	.7 - 4.2	M56886	M56986	14.73	11.56	.55	9.91	10.0 + .15	10.00
M6x1.0	4.2 - 6.6	M56887	M56987	17.27	11.56	.55	9.91	10.0 + .15	10.00
M8x1.25	.7 - 3.8	M56888	M56988	17.53	15.11	.55	13.46	13.5 + .15	13.50
M8x1.25	3.8 - 7.9	M56889	M56989	20.45	15.11	.55	13.46	13.5 + .15	13.50
M10x1.5	.7 - 3.8	M56890	M56990	17.53	15.11	.55	13.46	13.5 + .15	13.50
M10x1.5	3.8 - 7.9	M56891	M56991	20.45	15.11	.55	13.46	13.5 + .15	13.50

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
 Inch sizes are class 2B thread.
 Metric sizes are class 6H thread.

MSC Series Small Flange Closed End Ribbed Rivet Nuts

Available in Steel-Zinc Plated or Aluminum

MSC — Small Flange Ribbed Rivet Nut same as MSR with Closed End for complete thread seal. For use in moisture resistant applications. May install with all pneumatic and manual Rivet Nut tools.



MSC Series Small Flange Closed End Ribbed Rivet Nut

Thread Size	Grip Range Min-Max	Steel *Bulk Part #	Aluminum *Bulk Part #	A Body Length ±.015" ± 0.38 mm	B Head Dia. ±.010" ± 0.254 mm	C Head Height ±.003" ± 0.76 mm	D Body Dia. Max	Hole Size Min-Max	Drill Size Min-Max
6-32	.020 - .080	M26810	M36910	.740	.310	.019	.265	.265 - .271	17/64
6-32	.080 - .130	M26812	M36912	.740	.310	.019	.265	.265 - .271	17/64
8-32	.020 - .080	M26820	M36920	.740	.310	.019	.265	.265 - .271	17/64
8-32	.080 - .130	M26821	M36921	.740	.310	.019	.265	.296 - .302	17/64
10-24	.020 - .130	M26830	M36930	.990	.340	.019	.296	.296 - .302	19/64
10-24	.130 - .225	M26832	M36932	.990	.340	.019	.296	.296 - .302	19/64
10-32	.020 - .130	M26840	M36940	.990	.340	.019	.296	.296 - .302	19/64
10-32	.130 - .225	M26842	M36942	.990	.340	.019	.296	.296 - .302	19/64
1/4-20	.027 - .165	M26850	M36950	1.190	.455	.022	.390	.390 - .396	25/64
1/4-20	.165 - .260	M26854	M36954	1.190	.455	.022	.390	.390 - .396	25/64
1/4-28	.027 - .165	M26858	M36958	1.190	.455	.022	.390	.390 - .396	25/64
1/4-28	.165 - .260	M26859	M36959	1.190	.455	.022	.390	.390 - .396	25/64
5/16-18	.027 - .150	M26871	M36971	1.390	.595	.022	.530	.530 - .536	17/32
5/16-18	.150 - .312	M26874	M36974	1.390	.595	.022	.530	.530 - .536	17/32
5/16-24	.027 - .150	M26878	M36978	1.390	.595	.022	.530	.530 - .536	17/32
5/16-24	.150 - .312	M26879	M36979	1.390	.595	.022	.530	.530 - .536	17/32
3/8-16	.027 - .150	M26881	M36981	1.390	.595	.022	.530	.530 - .536	17/32
3/8-16	.150 - .312	M26882	M36982	1.390	.595	.022	.530	.530 - .536	17/32
3/8-24	.027 - .150	M26895	M36995	1.390	.595	.022	.530	.530 - .536	17/32
3/8-24	.150 - .312	M26896	M36996	1.390	.595	.022	.530	.530 - .536	17/32
M4x.07	.5 - 2.0	M26860	M36960	18.8	7.87	.48	6.73	6.75 + .15	6.75
M4x.07	2.0 - 3.3	M26865	M36965	18.8	7.87	.48	6.73	6.75 + .15	6.75
M5x0.8	.5 - 3.3	M26884	M36984	25.15	8.64	.48	7.52	7.6 + .15	7.60
M5x0.8	3.3 - 5.7	M26885	M36985	25.15	8.64	.48	7.52	7.6 + .15	7.60
M6x1.0	.7 - 4.2	M26886	M36986	30.23	11.56	.55	9.91	10.0 + .15	10.00
M6x1.0	4.2 - 6.6	M26887	M36987	30.23	11.56	.55	9.91	10.0 + .15	10.00
M8x1.25	.7 - 3.8	M26888	M36988	35.31	15.11	.55	13.46	13.5 + .15	13.50
M8x1.25	3.8 - 7.9	M26889	M36989	35.31	15.11	.55	13.46	13.5 + .15	13.50
M10x1.5	.7 - 3.8	M26890	M36990	35.31	15.11	.55	13.46	13.5 + .15	13.50
M10x1.5	3.8 - 7.9	M26891	M36991	35.31	15.11	.55	13.46	13.5 + .15	13.50

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
 Inch sizes are class 2B thread.
 Metric sizes are class 6H thread.

MHN Series Large Flange Half Hex Rivet Nuts

Available in Steel-Zinc Plated Threads

MHN — Large Flange Half Hex Rivet Nut provides exceptional torque-out strength and superior vibration resistance as the rivet nut external flat sides engage the hex cut opening. May be installed with all pneumatic and manual Rivet Nut tools.



MHN Series Large Flange Half Hex Rivet Nut

Thread Size	Grip Range Min-Max	Steel *Bulk Part #	A Body Length ±.015" ± 0.38 mm	B Head Dia. ±.010" ± 0.254 mm	C Head Height ±.003" ± 0.76 mm	D Body Dia. Max	Hex Hole Across Flats +.004"-.000"
6-32	.020 - .080	M52610	.385	.375	.027	.249	.250
6-32	.080 - .130	M52612	.435	.375	.027	.249	.250
8-32	.020 - .080	M52620	.385	.375	.027	.249	.250
8-32	.080 - .130	M52621	.435	.375	.027	.249	.250
10-24	.020 - .130	M52630	.435	.390	.027	.280	.281
10-24	.130 - .225	M52632	.535	.390	.027	.280	.281
10-32	.020 - .130	M52640	.435	.390	.027	.280	.281
10-32	.130 - .225	M52642	.535	.390	.027	.280	.281
1/4-20	.027 - .165	M52650	.585	.510	.030	.374	.375
1/4-20	.165 - .260	M52654	.685	.510	.030	.374	.375
5/16-18	.027 - .165	M52671	.685	.655	.035	.499	.500
5/16-18	.165 - .260	M52674	.845	.655	.035	.499	.500
3/8-16	.027 - .150	M52681	.685	.655	.035	.499	.500
3/8-16	.150 - .312	M52682	.845	.655	.035	.499	.500
M4x0.7	.5 - 2.0	M52660	9.78	9.53	.68	6.35	6.35
M5x0.8	2.0 - 3.3	M52665	11.05	9.53	.68	6.35	6.35
M5x0.8	.5 - 3.3	M52684	11.05	9.91	.68	7.1	7.14
M6x1.0	3.3 - 5.7	M52685	13.59	9.91	.68	7.1	7.14
M6x1.0	.7 - 4.2	M52686	14.86	12.96	.76	9.5	9.53
M8x1.25	4.2 - 6.6	M52687	17.40	12.96	.76	9.5	9.53
M8x1.25	.7 - 3.8	M52688	17.40	16.64	.89	12.7	12.7
M10x1.5	3.8 - 7.9	M52689	21.46	16.64	.89	12.7	12.7
M10x1.5	.7 - 3.8	M52690	17.40	16.64	.89	12.7	12.7
M10x1.5	3.8 - 7.9	M52691	21.46	16.64	.89	12.7	12.7

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
 Inch sizes are class 2B thread.
 Metric sizes are class 6H thread.

MQN Series Quad-Leg Rivet Nuts

Available in Steel-Zinc Plated Threads

MQN — Quad-Leg Rivet Nut is used for light duty, thin, or soft/brittle material... will accommodate slightly oversized hole with large back side footprint similar to a wall anchor. Utilizes dedicated manual tool for proper installation.



MQN Series Quad-Leg Rivet Nut


Thread Size	Grip Range Min-Max	Steel *Bulk Part #	A Overall Length	B Head Dia Ref	E Head Height (nom.)	D Body Dia. Max	Hole Size Min-Max	Drill Size
6-32	.000 - .197	M52510	.670	.472	.063	.315	.318 - .330	P (.323)
6-32	.197 - .394	M52511	.866	.472	.063	.315	.318 - .330	P (.323)
10-24	.000 - .197	M52530	.709	.547	.063	.394	.397 - .406	X (.397)
10-24	.197 - .394	M52532	.906	.547	.063	.394	.397 - .406	X (.397)
1/4-20	.000 - .197	M52550	.709	.630	.063	.472	.475 - .487	31/64
1/4-20	.197 - .394	M52554	.906	.630	.063	.472	.475 - .487	31/64
M4x0.7	.0 - 5.0	M52560	17.0	12.0	1.60	8.0	8.08 - 8.38	P (.323)
M4x0.7	5.0 - 10.0	M52565	22.0	12.0	1.60	8.0	8.08 - 8.38	P (.323)
M5x0.8	.0 - 5.0	M52584	18.0	13.9	1.60	10.0	10.08 - 10.31	X (.397)
M5x0.8	5.0 - 10.0	M52585	23.0	13.9	1.60	10.0	10.08 - 10.31	X (.397)
M6x1.0	.0 - 5.0	M52586	18.0	16.0	1.60	12.0	12.06 - 12.37	31/64
M6x1.0	.0 - 5.0	M52587	23.0	16.0	1.60	12.0	11.13 - 11.43	31/64

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
Inch sizes are class 2B thread. Metric sizes are class 6H thread.

MXN Series Large Flange Cross Bulb Rivet Nuts

Available in Steel-Zinc Plated Threads

MXN — Large Flange Cross Bulb Rivet Nut has large grip range with pre-bulb shank made up of 4 slots cut to rivet nut body providing large blindside footprint for greater pull out strength. Recommended for thin sheet metal and plastics and works well in oversized hole. May be installed with all pneumatic and manual Rivet Nut tools.



MXN Series Large Flange Cross Bulb Rivet Nut


Thread Size	Grip Range Min-Max.	Steel *Bulk Part #	A Body Length Min.-Max.	B Head Dia.	C Head Height	D Body Dia. Max.	Hole Size Min.-Max.	Drill Size
1/4-20	.020-280	M27150	.985 - 1.014	.610 - .645	.053 - .063	.382	.390-.396	25/64
1/4-20	.280-500	M27155	1.218 - 1.248	.610 - .645	.053 - .063	.382	.390-.396	25/64
5/16-18	.020-280	M27160	1.113 - 1.166	.740 - .770	.057 - .067	.495	.500-506	1/2
5/16-18	.280 - 500	M27161	1.359 - 1.390	.740 - .770	.057-.067	.495	.500-506	1/2
3/8-16	.020-280	M27162	1.205 - 1.233	.865 - .895	.083 - .093	.587	.594 - .600	#53
6MM	.5 - 7.1	M27151	25.02 - 25.78	15.49 - 16.38	1.35 - 1.60	9.7	10.0 - 10.15	X (.397)
6MM	7.1 - 12.7	M27156	30.96 - 31.72	15.49 - 16.38	1.35 - 1.60	9.7	10.0 - 10.15	X (.397)
8MM	.5 - 7.1	M27157	28.29 - 29.63	18.80 - 19.56	1.45 - 1.70	12.57	12.70 - 12.85	1/2
8MM	7.1 - 12.7	M27163	34.54 - 35.31	18.80 - 19.56	1.45 - 1.70	12.57	12.70 - 12.85	1/2
10MM	.5 - 7.1	M27164	30.61 - 31.32	21.97 - 22.73	2.11 - 2.36	14.91	15.09 - 15.24	#53

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
Inch sizes are class 2B thread. Metric sizes are class 6H thread.

MET Series External Thread Stud Rivet Nuts

Available in Steel-Zinc Plated Threads

MET — External Thread Stud Rivet Nut provides a strong external thread in blind applications. Allows for component mounting and mating nut. Easy to install with Spin/Spin and manual Tools using the proper external thread front end assembly.



MET Series External Thread Stud Rivet Nut

Thread Size	Grip Range Min-Max	*Steel Bulk Part #	A** Exposed Thread	B Head Dia. ±.010" ± .25 mm	L Body Length ±.020" ± .50 mm	C Head Height ±.003" ± .08 mm	D Body Dia. Max	Hole Size Min-Max	Drill Size
6-32	.020-.080	M28310	.500	.390	.485	.030	.265	.265 - .271	17/64
6-32	.080-.130	M28312	.450	.390	.535	.030	.265	.265 - .271	17/64
8-32	.020-.080	M28320	.450	.390	.485	.030	.265	.296 - .302	17/64
8-32	.080-.130	M28321	.450	.390	.535	.030	.265	.296 - .302	17/64
10-24	.020-.130	M28330	.500	.415	.545	.030	.296	.296 - .302	19/64
10-24	.130-.225	M28332	.405	.415	.655	.030	.296	.296 - .302	19/64
10-32	.020-.130	M28340	.500	.415	.545	.030	.296	.296 - .302	19/64
10-32	.130-.225	M28342	.405	.415	.655	.030	.296	.296 - .302	19/64
1/4-20	.027-.165	M28350	.625	.500	.670	.030	.390	.390 - .396	25/64
1/4-20	.165-.260	M28354	.530	.500	.770	.030	.390	.390 - .396	25/64
5/16-18	.027-.150	M28371	.625	.685	.810	.035	.530	.530 - .536	17/32
5/16-18	.150-.312	M28374	.463	.685	.925	.035	.530	.530 - .536	17/32
3/8-16	.027-.150	M28381	.750	.685	.810	.035	.530	.530 - .536	17/32
3/8-16	.150-.312	M28382	.588	.685	.925	.035	.530	.530 - .536	17/32
4mm	.50-2.00	M28360	12.0	9.91	12.32	.76	6.73	6.75 + .15	6.75
4mm	2.00-3.30	M28365	10.7	9.91	13.59	.76	6.73	6.75 + .15	6.75
5mm	.50-3.30	M28385	12.0	10.54	13.84	.76	7.52	7.6 + .15	7.6
5mm	3.30-5.70	M28384	9.6	10.54	16.64	.76	7.52	7.6 + .15	7.6
6mm	.70-4.20	M28386	15.0	12.7	17.02	.76	9.91	10.0 + .15	10.0
6mm	4.20-6.60	M28387	12.6	12.7	19.56	.76	9.91	10.0 + .15	10.0
8mm	.70-3.8	M28388	16.0	17.4	20.57	.89	13.46	13.5 + .15	13.5
8mm	3.8-7.90	M28389	11.9	17.4	23.5	.89	13.46	13.5 + .15	13.5
10mm	.70-3.8	M28390	20.0	17.4	20.57	.89	13.46	13.5 + .15	13.5
10mm	3.8-7.90	M28391	15.9	17.4	23.5	.89	13.46	13.5 + .15	13.5

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.

** Dimensions at maximum grip range.

Inch sizes are class 2B thread.

Metric sizes are class 6H thread.

MNN Series Neoprene Inserts

MNN — Neoprene Insert contains pre-molded brass nut for quick fastening in vibration, moisture protection, shock dampening, and even electrical insulation applications. Easy installation from blind side with conventional wrench. Just insert the proper thread screw or bolt and tighten.



MNN Series Neoprene Insert

Thread Size	Grip Range Min-Max	*Steel Bulk Part #	A Body Length ±.015" ± 0.38 mm	B Head Dia. ±.010" ± 0.254 mm	C Head Height ±.003" ± 0.76 mm	D Body Dia. Max	Hole Size Min-Max	Drill Size Min-Max
6-32	.015-.157	M52710	.496	.433	.055	.312	.312 - .323	5/16
8-32	.015-.157	M52720	.496	.433	.055	.312	.312 - .323	5/16
10-32	.015-.193	M52730	.555	.500	.035	.378	.378 - .386	W (.386)
10-32	.033-.232	M52731	.669	.551	.039	.378	.378 - .386	W (.386)
10-32	.031-.228	M52732	.709	.748	.079	.378	.378 - .386	W (.386)
10-32	.031-.228	M52733	.825	.746	.185	.378	.378 - .386	W (.386)
10-32	.031-.630	M52734	1.030	.551	.051	.378	.378 - .386	W (.386)
10-32	.311-.449	M52735	.846	.551	.035	.378	.378 - .386	W (.386)
10-32	.984-1.256	M52736	1.732	.551	.035	.378	.378 - .386	W (.386)
1/4-20	.015-.110	M52750	.630	.630	.051	.500	.500 - .508	1/2
1/4-20	.031-.185	M52751	.831	.750	.187	.500	.500 - .508	1/2
1/4-20	.252-.453	M52752	1.051	.642	.079	.500	.500 - .508	1/2
1/4-20	.453-.906	M52753	1.377	.630	.051	.512	.512 - .520	33/64
5/16-18	.015-.157	M52771	.720	.847	.126	.626	.626 - .634	41/64
5/16-18	.156-.374	M52772	1.099	.847	.225	.626	.626 - .634	41/64
5/16-18	.079-.709	M52773	1.970	.787	.063	.750	.750 - .758	3/4
3/8-16	.748-1.570	M52781	2.165	.886	.051	.750	.750 - .758	3/4
1/2-13	1.470-1.575	M52791	3.070	1.060	.051	.945	.945 - .953	61/64
M3-0.5	.04-4.0	M52810	12.6	11.0	1.4	7.9	7.90 - 8.20	7.9
M4-0.7	.4-4.0	M52820	12.6	11.0	1.4	7.9	7.90 - 8.20	7.9
M5-0.8	.4-4.9	M52830	14.1	12.7	.9	9.6	9.60 - 9.80	9.6
M5-0.8	.85-5.9	M52831	17.0	14.0	1.0	9.6	9.60 - 9.80	9.6
M5-0.8	.8-5.8	M52832	18.0	19.0	2.0	9.6	9.60 - 9.80	9.6
M5-0.8	.8-5.8	M52833	20.95	18.95	4.7	9.6	9.60 - 9.80	9.6
M5-0.8	7.9-16	M52834	26.1	14.0	1.3	9.6	9.60 - 9.80	9.6
M5-0.8	7.9-11.4	M52835	21.5	14.0	.9	9.6	9.60 - 9.80	9.6
M5-0.8	20.5-30	M52836	39.8	14.0	1.3	9.6	9.60 - 9.80	9.6
M6-1.0	.4-2.8	M52850	16.0	16.0	1.3	12.7	12.7 - 12.9	1/2
M6-1.0	.8-4.7	M52851	21.1	19.05	4.75	12.7	12.7 - 12.9	1/2
M6-1.0	6.4-11.5	M52852	26.7	16.3	2.0	12.7	12.7 - 12.9	1/2
M6-1.0	11.5-23	M52853	35.0	16.0	1.3	13.0	13.0 - 13.20	13.0
M8-1.25	.4-4.0	M52871	18.3	21.5	3.2	15.9	15.9 - 16.1	16.0
M8-1.25	3.95-9.5	M52872	27.93	21.5	5.72	15.9	15.9 - 16.1	16.0
M8-1.25	2.0-18.0	M52873	50.0	20.0	1.6	18.0	18.0 - 18.2	18.0
M10-1.5	19.0-40.0	M52881	55.0	22.5	1.3	15.9	20.0 - 20.2	20.0
M12-1.75	36.0-64.0	M52891	78.0	27.0	1.3	15.9	24.0 - 24.2	24.0

Dimensions in green indicate millimeters (mm) * Also available in small packaged quantities.
Inch sizes are class 2B thread. Metric sizes are class 6H thread.

Rivet Nut Tools & Kits



Rivet Nut Setter™ RN-1/M39300

Capable of installing all sizes of rivet nuts and threaded inserts up to 1/4-20 and 6mm threads in steel, the next-generation Rivet Nut Setter features a quick-change mandrel and longer handles for improved leverage and an adjustable stroke, positive-stop locking feature. Rivet Nut Setter is ergonomically designed, with a forged, heat-treated steel upper handle, precision die-cast body of high-strength aluminum alloy, patented fulcrum pin design, and comfortable hand grips. Supplied with 8-32, 10-24 and 10-32 mandrels and nosepieces. Available in a variety of kit forms. Weight: 1.2 lbs.



Rivet Nut Kit/M39301

Model M39301 Rivet Nut Kit contains the M39300 Rivet Nut tool in a molded plastic case; mandrels and nosepieces for 6-32, 8-32, 10-24 and 1/4-20, instructions and wrench. The kit also includes 103 assorted Klik Rivet Nuts and Klik Poly-Nuts: 25 each M57210, M57425, M57130; 20 each M57250; 8 each M57445. Weight: 2.75 lbs.

Poly-Nut Kit/M39302

Model M39302 Poly-Nut Kit contains the M39300 Rivet Nut tool in a molded plastic case with 8-32, 10-32 and 1/4-20 mandrels and nosepieces, wrench and instructions. The kit contains 52 assorted Klik Poly-Nuts: 12 each M57425, M57435, M57445; 16 each M57455. Weight: 3 lbs.

Metric Poly-Nut Kit/M39303

Model M39303 Metric Poly-Nut Kit contains the M39300 Rivet Nut tool in a molded plastic case with 4mm, 5mm, 6mm and 8mm mandrels and nosepieces, wrench and instructions. The kit contains 75 assorted Klik Poly-Nuts: 25 each M57407, M57409; 15 each M57411; 10 each M57413. Weight: 3.25

Mandrel/Nosepiece Chart

Thread Size	Mandrel No.	Nosepiece No.	Kit No.
6-32	M39354	M39361	M39380
8-32	M39355	M39362	M39381
10-24	M39356	M39363	M39382
10-32	M39357	M39363	M39383
1/4-20	M39358	M39379	M39379
1/4-28	M39371	M39379	M39384
5/16-18*	M39359	Not Needed	
5/16-24*	M39372	Not Needed	
3/8-16*	M39360	Not Needed	
4mm	M39366	M39374	M39385
5mm	M39367	M39373	M39386
6mm	M39368	M39375	M39387
8mm	M39369	Not Needed	

For tool RN-1 M39300

*Not recommended for steel rivet nut.

Ribbed Rivet Nut Kit/M39315

Model M39215 Ribbed Rivet Nut kit contains the M39300 Rivet Nut tool in a molded plastic case; mandrels, nosepieces, wrench & instructions for setting 8-32, 10-24, 10-32 and 1/4-20 Rivet Nuts. The kit also includes 50 assorted Ribbed style Rivet Nuts: 12 each M57320, M57330, M57340; 8 each M57350; 6 each M57354. Weight: 2.75 lbs.

Metric Ribbed Rivet Nut Kit/M39316

Model M39316 Ribbed Rivet Nut kit contains the M39300 Rivet Nut tool in a molded plastic case with 4mm, 5mm, 6mm and 8mm mandrels and nosepieces, wrench and instructions. The kit also includes 50 assorted Ribbed style Rivet Nuts: 12 each M57360, M57385, M57384; 8 each M57386; 6 each M57387. Weight: 2.75 lbs.

Steel Klik Thread-sert Kit/M39314

Model M39314 Thread-sert Kit contains the M39300 Rivet Nut tool in a plastic case with 6-32, 8-32, 10-24, 10-32, 1/4-20, 5/16-18 and 3/8-16 mandrels and nosepieces, wrench and instructions. The kit contains 62 assorted Steel Klik Thread-serfs: 10 each M57810, M57820, M57830, M57840, M57850; 6 each M57871, M57881. Weight: 3.25 lbs.

Aluminum Klik Thread-sert Kit/M39313

Model M39313 Thread-sert Kit contains the M39300 Rivet Nut tool in a molded plastic case with 6-32, 8-32, 10-24, 10-32, 1/4-20, 5/16-18 and 3/8-16 mandrels and nosepieces, wrench and instructions. The kit contains 62 assorted Aluminum Klik Thread-serfs: 10 each M57910, M57920, M57930, M57940, M57950; 6 each M57971, M57981. Weight: 3 lbs.

Quad Leg Nut Installation Tool (MJN-1/M39042)

New from Marson, the MJN-1 hand-held Quad Leg Nut Installation tool is designed to effortlessly set quad leg nuts and Jack Nuts® in sizes ranging from 6-32 – 1/4-20, and M4 – M6. It works by threading the bolt to the quad leg nut, then dropping the component in the slot of the tool, inserting it into the pre-drilled hole, and squeezing until set. Pressing the release lever releases the tool. Then tightening the exposed bolt completes the installation.

Jack Nut® is a registered trademark of The Black & Decker Corporation.



325RN/M34604

Choose the M34604 for installing larger size Rivet Nuts. Model M34604 is a heavy-duty tool that will install 10-24 through 3/8"-16, and 5mm through 10mm threaded inserts in aluminum or steel. Quick-change mandrels, easily adjustable stroke. Supplied with 1/4"-20 mandrel and nosepiece only. Weight: 4.25 lbs.

325RNK Kit/M34606

The M34606 / 325RNK kit comes complete with the heavy-duty 325RN Rivet Nut tool, mandrels and nosepieces to set 10-24", 10-32", 1/4-20", 5/16-18" and 3/8-16" Rivet-Nuts, and service/adjustment tools all contained within a sturdy carrying case. Optional external thread adapters available.



NEW

425RN/M34607

Like the 325RN, the 425RN will install the full range of Rivet Nuts. It offers quick-change mandrels, easy adjust stroke, and a fast-action Push/Pull plunger that can be used to spin on and spin off rivet nuts for more speed. Supplied with 1/4-20 mandrel and nosepiece only. Weight 4.5 lbs.

425RNK Kit/M34008

The M34008 / 425RNK kit comes complete with the heavy-duty 425RN Rivet Nut tool, mandrels and nosepieces to set 10-24", 10-32", 1/4-20", 5/16-18" and 3/8-16" Rivet-Nuts, and service/adjustment tools all contained within a sturdy carrying case. Optional external thread adapters available.



NEW

Mandrel/Nosepiece Chart for M34604 and M34607

Thread Size	Mandrel No.	Nosepiece No.	Mandrel/Nosepiece Combo No.	MET External Thread
10-24	M95635	M95645	M34615	M34635
10-32	M95636	M95645	M34616	M34636
1/4-20	M95637	M95647	M34617	M34637
5/16-18	M95638	M95648	M34618	M34638
3/8-16	M95639	M95649	M34619	—
5mm	M95630	M95640	M34625	M34645
6mm	M95631	M95641	M34626	M34647
8mm	M95632	M95642	M34627	M34648
10mm	M95633	M95643	M34628	—

Rivet Nut Tools & Kits



140-SP/M39223

The 140-SP features Spin/Pull action in a smaller tool. Just hold the Rivet Nut onto the mandrel end and engage. The tool will automatically spin the nut on. Insert the Rivet Nut in the hole and pull the trigger to set the fastener. Then toggle to the bottom trigger and reverse spin the mandrel off. Easy installation in seconds. Comes supplied with inch and metric mandrels and nosepieces 6-32 through 1/4-20 and 4mm though 6mm, all conveniently stored in a durable carry case. Weight 4.9 lbs.

Mandrel Nosepiece Chart for 140-SP/M39223

Thread Size	Mandrel No.	Nosepiece No.
6-32	M88708	M88701
8-32	M88709	M88702
10-24	M88710	M88703
10-32	M88711	M88703
1/4-20	M88712	M88704
4mm	M88651	M88646
5mm	M88652	M88647
6mm	M88653	M88648

Mandrel Nosepiece Chart for 160-SP/M39225

Thread Size	Mandrel No.	Nosepiece No.
6-32	M71345403	M71345396
8-32	M71345404	M71345397
10-24	M71345405	M71345398
10-32	M71345406	M71345398
1/4-20	M71345407	M71345399
5/16-18	M71345408	M71345400
3/8-16	M71345409	M71345401
1/2-13	M71345410	M71345402

Metric Mandrel Nosepiece Chart for 160-SP/M39226

Thread Size	Mandrel No.	Nosepiece No.
4mm	M71C00277	M713287
5mm	M71C00278	M713288
6mm	M71C00279	M713289
8mm	M71C00514	M713290
10mm	M71C00281	M713291
12mm	M713177	M713292



160-SP/M39225

The new Marson 160-SP Spin/Pull rivet nut setting tool is our most powerful air/hydraulic rivet nut tool yet. Engage the rivet nut onto the mandrel, and the 160-SP automatically threads the fastener on the tool. Pressing and holding the trigger in position will set the rivet nut and reverse itself out automatically, all in one operation.

This advanced tool features an adjustable stroke knob in the base of the tool to fully adjust stroke length to suit any grip range. Included is a swivel air inlet for increased mobility. For added convenience, adjustments and changes are performed outside the tool, with no required tear down to adjust the stroke or change thread sizes.

Comes supplied with either all inch (M39225) or all metric (M39226) mandrels and nosepieces conveniently stored in a durable carry case. Weight 6 lbs.

SST Series

The versatile, low cost, Spin/Spin pneumatic rivet nut production tool now comes with a quick-change nosepiece assembly and standard socket head cap screw for convenient replacement and change over. For added ease of operation, the Spin/Spin offers a superior ergonomic design, lightweight body, and operates without stroke adjustment. Available models come with 2 front assemblies of your choice (refer to table below).

NEW



Additional nosepiece and mandrel sizes are available:

SST-1/M39801 - 3000 RPM
SST-2/M39802 - 1500 RPM
SST-3/M39803 - 600 RPM
SST-4/M39804 - 400 RPM

Marson Spin/ Tool Model Thread Size	3000 RPM SST-1 Recommended	1500 RPM SST-2		600 RPM SST-3		400 RPM SST-4 Recommended
		Recommended	Optional	Recommended	Optional	
4-40	✓					
6-32	✓					
8-32	✓		✓			
10-24		✓			✓	
10-32		✓			✓	
1/4-20			✓	✓		
1/4-28			✓	✓		
5/16-18					✓	✓
5/16-24					✓	✓
3/8-16						✓
3/8-24						✓
M3	✓					
M4	✓		✓			
M5		✓			✓	
M6			✓	✓		
M8					✓	✓
M10						✓

OPERATOR IS LIABLE FOR CORRECT AIR PRESSURE. DO NOT EXCEED 100 PSI.

Purchasing the Optional Front End Assemblies are at the Owner's discretion. Care must be taken to optimize the tools Rivet Nut setting ability. Adjustment of the air pressure will be necessary in order for the tool to function in both minimum and maximum capacity on ALL optional thread sizes per tool. Available retrofit for MET external thread, contact customer service.

Rivet Nut Tools & Kits

Spin/Spin Front End Assembly Table

Recommended Tool	Inch Size	Front End Assembly FEA #	Anvil / Nosepiece	3 Bearing Set	Hex-drive	Mandrel / Screw Thread
M39801	4-40	M95500	M95399	M95525	M95535	M95424
M39801	6-32	M95501	M95400	M95526	M95536	M95425
M39801	8-32	M95502	M95401	M95527	M95537	M95426
M39802	10-24	M95503	M95402	M95528	M95538	M95427
M39802	10-32	M95504	M95402	M95528	M95538	M95428
M39803	1/4-20	M95505	M95404	M95529	M95539	M95429
M39803	1/4-28	M95506	M95404	M95529	M95539	M95430
M39804	5/16-18	M95507	M95406	M95530	M95540	M95431
M39804	5/16-24	M95508	M95406	M95530	M95540	M95432
M39804	3/8-16	M95509	M95408	M95531	M95541	M95433
M39804	3/8-24	M95510	M95408	M95531	M95541	M95434

Contact customer service for MET series front ends.

Recommended Tool	Metric Size	Front End Assembly FEA #	Anvil / Nosepiece	3 Bearing Set	Hex-drive	Mandrel / Screw Thread
M39801	M3	M95515	M95400	M95526	M95545	M95440
M39801	M4	M95516	M95401	M95527	M95546	M95441
M39802	M5	M95517	M95402	M95528	M95547	M95442
M39803	M6	M95518	M95404	M95529	M95548	M95443
M39804	M8	M95519	M95406	M95530	M95549	M95444
M39804	M10	M95520	M95408	M95531	M95550	M95445

Inch-Metric Conversion Table

Inches			Inches		
Fraction	Decimal	mm	Fraction	Decimal	mm
1/64	.015 625	.3969	33/64	.515 625	13.0969
1/32	.031 250	.7938	17/32	.531 250	13.4938
3/64	.046 875	1.1906	35/64	.546 875	13.8906
1/16	.062 500	1.5875	9/16	.562 500	14.2875
5/64	.078 125	1.9844	37/64	.578 125	14.6844
3/32	.093 750	2.3812	19/32	.593 750	15.0812
7/64	.109 375	2.7781	39/64	.609 375	15.4781
1/8	.125 000	3.1750	5/8	.625 000	15.8750
9/64	.140 625	3.5719	41/64	.640 625	16.2719
5/32	.156 250	3.9688	21/32	.656 250	16.6688
11/64	.171 875	4.3656	43/64	.671 875	17.0656
3/16	.187 500	4.7625	11/16	.687 500	17.4625
13/64	.203 125	5.1594	45/64	.703 125	17.8594
7/32	.218 750	5.5562	23/32	.718 750	18.2562
15/64	.234 375	5.9531	47/64	.734 375	18.6531
1/4	.250 000	6.3500	3/4	.750 000	19.0500
17/64	.265 625	6.7469	49/64	.765 625	19.4469
9/32	.281 250	7.1438	25/32	.781 250	19.8437
19/64	.296 875	7.5406	51/64	.796 875	20.2406
5/16	.312 500	7.9375	13/16	.812 500	20.6375
21/64	.328 125	8.3344	53/64	.828 125	21.0344
11/32	.343 750	8.7312	27/32	.843 750	21.4312
23/64	.359 375	9.1281	55/64	.859 375	21.8281
3/8	.375 000	9.5250	7/8	.875 000	22.2250
25/64	.390 625	9.9219	57/64	.890 625	22.6219
13/32	.406 250	10.3188	29/32	.906 250	23.0188
27/64	.421 875	10.7156	59/64	.921 875	23.4156
7/16	.437 500	11.1125	15/16	.937 500	23.8125
29/64	.453 125	11.5094	61/64	.953 125	24.2094
15/32	.468 750	11.9062	31/32	.968 750	24.6062
31/64	.484 375	12.3031	63/64	.984 375	25.0031
1/2	.500 000	12.7000	1	1.000 000	25.4000

Decimal Equivalents of Standard Sheet Gauges

Inches No. of Gauge	Thickness in Thousandths	
	Aluminum (B & S)	Steel (U.S. Std.)
10	.1019	.1345
11	.0907	.1196
12	.0808	.1046
13	.0720	.0897
14	.0641	.0747
15	.0571	.0673
16	.0508	.0598
17	.0453	.0538
18	.0403	.0478
19	.0359	.0418
20	.0320	.0359
21	.0285	.0329
22	.0253	.0299
23	.0226	.0269
24	.0201	.0239
25	.0179	.0209
26	.0159	.0179
27	.0142	.0164
28	.0126	.0149
29	.0113	.0135
30	.0100	.0120

Alcoa Fastening Systems



For more than 120 years, the name Alcoa has been recognized worldwide as a strong leader in product quality and customer support. These strengths are found in every product manufactured for Alcoa Fastening Systems, offering the greatest breadth and depth of fastening system solutions in the industry.

Alcoa Fastening Systems (AFS) maintains company offices in the United States and in many other countries. AFS fastener distributors are also located in many of the world's industrial centers, where they provide a ready source of AFS fasteners, installation tools, tool parts, and application assistance.

Americas

Industrial Fastener Division
8001 Imperial Drive
Waco, TX 76712, USA
P.O. Box 8117
Waco, TX 76714-8117, USA
Tel: 800 388 4825
Fax: 800 798 4825

Installation Tool Division
1 Corporate Drive
Kingston, NY 12401, USA
Tel: 800 278 4825
Fax: 845 334 7333

AFS Industrial Distribution
Group Headquarters
1925 North MacArthur Drive
Tracy, CA 95376, USA
Tel: 209 839 3000
Fax: 209 839 3022

AFS Industrial
Distribution Group
5436 West 78th Street
Indianapolis, IN 46268, USA
Tel: 800 826 2884
Fax: 800 573 2645

Latin America Sales
Avenida Parque Lira
79-402 Tacubaya
Mexico C P 11850, USA
Tel: +52 55 5515 1776
Fax: +52 55 5277 7564

International Locations

India Operations
Level 6, Constantia 11
U.N. Brahmachari Street
Kolkata 700,017 WB India
Tel: +91 33 4400 0612
Fax: +91 33 4400 0555

Japan/Korea Sales
Alcoa Japan Ltd.
#1013 NBF Hibiya Bldg.
Uchisaiwai-cho, Chiyoda-ku
Tokyo 100-1011
Phone: +81 3 3539 6577
Fax: +81 3 3539 6585

Melbourne Operations
1508 Centre Road
Clayton, Victoria, 3168
Australia
Tel: +61 3 8545 3333
Fax: +61 3 8545 3390

Shanghai Sales
Area A2, 1st Floor
No. 205 Taigu Road
Waigaocqiao Free Trade Zone
Shanghai, 200131, China
Tel: +86 21 5866 5080
Fax: +86 21 5868 1859

Telford Operations
Unit C, Stafford Park 7
Telford, Shropshire TF3, 3BQ
United Kingdom
Tel: +44 1952 2900 11
Fax: +44 1952 2904 59

Alcoa Fastening Systems
St Cosme Operations
9 rue de Cressonnieres
72110 Saint Cosme en Varais
France
Tel: +33 0 2.43.31.41.00
Fax: +33 0 2.43.31.41.41

Alcoa Fastening Systems
Kelkheim Operations
Industriestr. 6
65779 Kelkheim
Germany
Tel: +49 0 6195 8050
Fax: +49 0 6195 2001

alcoafasteners.com
afs-idg.com

Disclaimer:

The information contained in this publication is only for general guidance, and is not intended to create any warranty, express, implied, or statutory; all warranties are contained only in AFS's written quotations, acknowledgments, and/or purchase orders. It is recommended that the user secure specific, up-to-date data and information regarding each application and/or use of such products.

**Alcoa
Fastening
Systems**

