

NOTE:

- GRIP RANGE: .150 .312 HOLE SIZE: .531 +.006/-.000 AFTER ALL APPLIED FINISHES. INSTALLED LENGTH: .425 MAX. 2.
- 3.
- 4. LUBRICATION: WAX
- INSTALLATION TOOL: SSG 803 SPIN SPIN

	TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.	NEXT ASSY	USED ON	FINISH ZINC PLATE YELLOW DICHROMATE PER ASTM B633 Fe/Zn 8um TYPE II	E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		SIZE DWG. NO. CAL2-3118-312		2	A	
	PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CON-			MATERIAL C1008/1010	Q.A. COMMENTS:			SIZE DWG. NO. REV			
				TOLERANCES: ANGULAR: MACH±1 BEND±1 TWO PLACE DECIMAL±01 THREE PLACE DECIMAL±002 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	MFG APPR.	AJP	11/3/06	TITLE:)
					ENG APPR.	TOO	11/3/06				
					CHECKED						
					DRAWN	TOO	11/3/06				
				UNLESS OTHERWISE SPECIFIED:		NAME	DATE		_		

3

2