




NOTE:

1. GRIP RANGE: 4.2 - 6.6
2. HOLE SIZE: 10.00 +0.15/-0.0 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: 9.65 MAX.
4. LUBRICATION: WAX
5. INSTALLATION TOOL: SSG 802 SPIN SPIN

PROPRIETARY AND CONFIDENTIAL
THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX, AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH± 1 BEND ±1 ONE PLACE DECIMAL ±0.10 TWO PLACE DECIMAL ±0.05	DRAWN	TOO	7/20/05	TITLE: LARGE FLANGE OPEN END			
			CHECKED						
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG APPR.	TOO	7/20/05				
			MFG APPR.	AJP	7/20/05				
		MATERIAL C1008/C1010	Q.A.						
			COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358			SIZE	DWG. NO. A CAL2-610-6.6		REV A
NEXT ASSY	USED ON	FINISH ZINC PLATE YELLOW DICHROMATE PER ASTM B633 Fe/Zn 8um TYPE II				SCALE: 2:1		WEIGHT: .0050 kg	SHEET 1 OF 1
APPLICATION		DO NOT SCALE DRAWING							