







SECTION A-A



NOTE:

1. GRIP RANGE: .020 - .280
2. HOLE SIZE: .393 +.006/-.000 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: .505 REF.
4. LUBRICATION: WAX
5. INSTALLATION TOOL: SSG 802 SPIN SPIN

PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX, AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY. SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
			DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002	DRAWN	TOO	5/23/05	
			INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED			
			MATERIAL C1008/C1010	ENG APPR.	TOO	5/23/05	
			FINISH ZINC PLATE YELLOW DICHROMATE PER ASTM B633 Fe/Zn 8um TYPE II	MFG APPR.	AJP	5/23/05	
	NEXT ASSY	USED ON		Q.A.			TITLE: PREBULBED SLOTTED BODY
	APPLICATION	DO NOT SCALE DRAWING		COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358			
							SIZE DWG. NO. REV A CPB2-2520-280 A
							SCALE: 2:1 WEIGHT: .0071 kg SHEET 1 OF 1